# **Attachment 86**

Memo from JCAR accepting Second Notice dated April 15, 2011

CO-CHAIR: SEN. MAGGIE CROTTY

CO-CHAIR: REP. ANGELO "SKIP" SAVIANO

EXECUTIVE DIRECTOR: VICKI THOMAS



700 STRATTON BUILDING SPRINGFIELD, ILLINOIS 62706 217/785-2254 SEN. PAMELA ALTHOFF
SEN. DON HARMON
SEN. JOHN O. JONES
SEN. DALE RIGHTER
SEN. IRA SILVERSTEIN
REP. GREGORY HARRIS
REP. LOU LANG
REP. DONALD MOFFITT
REP. ROSEMARY MULLIGAN
REP. ANDRÉ THAPEDI

# **MEMORANDUM**

RECEIVED

Division of Legal Counsel

TO:

Douglas Scott, Director

Environmental Protection Agency

APR 1 8 2011

FROM:

Vicki Thomas

Executive Director

Environmental Protection

Agency

DATE:

4/15/11

RE:

Procedures to be Followed in the Performance of Inspections of Motor Vehicle

Emissions (35 Ill. Adm. Code 276)

35 Ill. Reg. 14 - 1/3/11

The Office of the Joint Committee on Administrative Rules has accepted the Second Notice for the above-referenced rulemaking. The Second Notice period began on 4/15/11 and ends no later than 5/29/11, unless extended pursuant to Section 5-40 of the IAPA.

This rulemaking is scheduled to be considered by JCAR at its 5/10/11 meeting, Stratton Office Building, Springfield, IL at a time yet to be determined. Staff will be contacting you if they have questions concerning this rulemaking and will advise you of any change in time or location of the Committee meeting.

Please contact us if you have any questions regarding the JCAR review procedure.

VT:DC:rm

cc:

Kent Mohr

Adm. Code Div.

# **Attachment 87**

JCAR's Certification of No Objection Second Notice changes dated May 10, 2011

ILLINOIS GENERAL ASSEMBLY

CO-CHAIR: SEN, MAGGIE CROTTY

CO-CHAIR: REP. ANGELO "SKIP" SAVIANO

EXECUTIVE DIRECTOR: VICKI THOMAS



700 STRATTON BUILDING SPRINGFIELD, ILLINOIS 62706 217/785-2254 SEN. PAMELA ALTHOFF
SEN. DON HARMON
SEN. JOHN O. JONES
SEN. DALE RIGHTER
SEN. IRA SILVERSTEIN
REP. GREGORY HARRIS
REP. LOU LANG
REP. DONALD MOFFITT
REP. ROSEMARY MULLIGAN
REP. ANDRÉ THAPEDI

# JOINT COMMITTEE ON ADMINISTRATIVE RULES

# CERTIFICATION OF NO OBJECTION TO PROPOSED RULEMAKING

This is to certify that the Joint Committee on Administrative Rules, at its 5/10/11 meeting, considered a rulemaking titled Procedures to be Followed in the Performance of Inspections of Motor Vehicle Emissions (35 Ill. Adm. Code 276; 35 Ill. Reg. 14), proposed by the Environmental Protection Agency and published in the 1/3/11 issue of the Illinois Register. After consideration, and based upon the agreements, if any, for modification of the rulemaking made by the agency and attached to this document, the Committee determined that no Objection will be issued to the above mentioned rulemaking.

Vicki Thomas
Executive Director

5/10/11

Attachments: Agreements

Recommendation Issued

# SECOND NOTICE CHANGES

Agency:

Environmental Protection Agency

Rulemaking:

Procedures to Be Followed in the Performance of Inspection of Motor

Vehicle Emissions (35 Ill. Adm. Code 276; 35 Ill. Reg. 14)

# Changes:

- 1. In line 206, delete "either".
- 2. In lines 210, 285, 425 and 464, strike "which" and add "that".
- 3. In line 257, strike"(fuel cap tester)" and before "means" add "or "fuel cap tester"".
- 4. In line 349, strike "(MIL)" and a before "means" add "or "MIL"".
- 5. In line 357, strike"(NIST)" and before "means" add "or "NIST gas"".
- 6. In line 440, delete "(TBD)" and before "means" add "or "TBD"".
- 7. In line 450, delete "TED" and before "means" add "or "TED"".
- 8. In line 501, after "1994)" add a period.
- 9. In line 600, strike "which" and add "that".
- 10. In line 671, strike "subsections" and add "subsection".
- 11. In line 839, strike "which" and add "that".
- 12. In line 1282, strike the 1st comma and add "and".
- 13. In line 1709, delete the 2<sup>nd</sup> "276.405".
- 14. In line 2042, after "required" add ", upon request".
- 15. In line 2330, change "specified by the Agency" to "specified in the fleet inspection agreement referenced in Section 276.702(c)(2)".
- 16. In line 2340, after "that" add a comma.

- 17. In lines 2341 and 2477, strike "such" and add "the".
- 18. In line 2495, change "shall" to "will".
- 19. In line 2504, strike the 1<sup>st</sup> "and".
- 20. In line 2505, after "and" add "that".
- 21. In line 2560, after "law" add "or rule".
- 22. In lines 2564 and 2567-2568, delete "Illinois Environmental Protection".
- 23. In lines 2590 and 2645, delete "by".

5/9/11

# **Attachment 88**

Notice of Adopted Amendments filed and effective June 28, 2011 Illinois Register publication 35 Ill. Reg. 11268 July 15, 2011

# 2011


# REGISTER

RULES OF GOVERNMENTAL AGENCIES

Volume 35, Issue 29

July 15, 2011

Pages 11032-12186



Index Department
Administrative Code Division
111 E. Monroe St.
Springfield, IL 62756
217-782-7017
www.cyberdriveillinois.com

Printed on recycled paper

Printed by authority of the State of Illinois. July 2011---90

PUBLISHED BY JESSE WHITE • SECRETARY OF STATE



# NOTICE OF ADOPTED AMENDMENTS

- 1) <u>Heading of the Part</u>: Procedures to be Followed in the Performance of Inspections of Motor Vehicle Emissions
- 2) <u>Code Citation</u>: 35 Ill. Adm. Code 276

2)	Castian Namel	A .I 4 . I .A 4
3)	Section Numbers:	Adopted Action:
	276.101	Amended
	276.102	Amended
	276.103	Amended
	276.104	Amended
	276.201	Amended
	276.203	Amended
	276.204	Amended
	276.205	Amended
	276.207	Repealed
	276.209	Amended
	276.301	Amended
	276.303	Amended
	276.304	Repealed
	276.305	Repealed
	276.306	Repealed
	276.307	Repealed
	276.308	Repealed
	276.309	Repealed
	276.310	Repealed
	276.311	Repealed
	276.312	Repealed
	276.401	Amended
	276.403	Amended
	276.404	Amended
	276.405	New
	276.501	Amended
	276.502	Amended
	276.503	Amended
	276.504	Amended
	276.505	Repealed
	276.506	Repealed
	276.507	Amended
	2,0.007	1 xiiioiided

# NOTICE OF ADOPTED AMENDMENTS

276.602       Amended         276.604       Amended         276.605       Repealed         276.701       Amended         276.702       Amended         276.703       Amended         276.704       Amended         276.802       Amended         276.803       Amended         276.901       Amended         276.902       Amended         276.903       Repealed	d d d d
276.605       Repealed         276.701       Amended         276.702       Amended         276.703       Amended         276.704       Amended         276.802       Amended         276.803       Amended         276.901       Amended         276.902       Amended	d d
276.701       Amended         276.702       Amended         276.703       Amended         276.704       Amended         276.802       Amended         276.803       Amended         276.901       Amended         276.902       Amended	d d
276.702       Amendee         276.703       Amendee         276.704       Amendee         276.802       Amendee         276.803       Amendee         276.901       Amendee         276.902       Amendee	d
276.703       Amendee         276.704       Amendee         276.802       Amendee         276.803       Amendee         276.901       Amendee         276.902       Amendee	
276.704       Amendee         276.802       Amendee         276.803       Amendee         276.901       Amendee         276.902       Amendee	1
276.802       Amendee         276.803       Amendee         276.901       Amendee         276.902       Amendee	
276.803       Amended         276.901       Amended         276.902       Amended	d
276.901 Amendee 276.902 Amendee	d
276.902 Amended	d
	d
276.903 Repealed	d
2,3,333	1
276.1001 Amended	d
276.1002 Amended	d
276.II01 New	
276.TABLE A Repealed	
276.TABLE B Repealed	ł

- 4) <u>Statutory Authority</u>: Section 13C-10 and 13C-20 of the Vehicle Emissions Inspection Law of 2005 [625 ILCS 5/13C-10 and 13C-20]
- 5) Effective Date of Amendments: June 28, 2011
- 6) Does this rulemaking contain an automatic repeal date? No
- 7) Does this rulemaking contain incorporations by reference? Yes
- 8) A copy of the adopted amendments, including any material incorporated by reference. is on file in the Illinois Environmental Protection Agency's principal office and is available for public inspection.
- 9) Notice of Proposal Published in the Illinois Register: January 3, 2011; 35 Ill. Reg. 14
- 10) Has JCAR issued a Statement of Objection to this rulemaking? No
- I1) <u>Difference between proposal and final version</u>: Minor grammar and formatting changes were made.

#### NOTICE OF ADOPTED AMENDMENTS

In Section 276.604, after "required", added ", upon request".

In Section 276.704(a), "specified by the Agency" was changed to "specified in the fleet inspection agreement referenced in Section 276.702(c)(2)".

- Have all the changes agreed upon by the agency and JCAR been made as indicated in the agreements issued by JCAR? Yes
- 13) Will this rulemaking replace any emergency rulemaking currently in effect? No
- 14) Are there any amendments pending on this Part? No
- 15) Summary and Purpose of Amendments: The Illinois Environmental Protection Agency's (Illinois EPA) amendments to Part 276 reflect the adoption of the Vehicle Emissions Inspection Law of 2005 ("VEIL of 2005") (PA 94-526) (625 ILCS 5/13C), an amendment to the VEIL of 2005 (PA 94-848), and necessary improvements to the program. The amendments remove definitions relating to the removal of the IM240 emissions test, add new definitions and clarify other definitions. The amendments remove the IM240 emissions test procedures, related provisions, and all references thereto to reflect full implementation of OBD testing. The amendments require a subject vehicle owner to obtain, but not display or possess, an emissions compliance certificate in order to obtain or renew the subject vehicle's registration. The amendments specify the design of an emissions compliance certificate. The amendments remove all different types of inspection certificates or stickers and utilize a universal "emission compliance certificate." The amendments clarify the recordkeeping requirements relating to maintenance and calibrations performed. The amendments revise provisions relating to waivers, economic hardship, fleet self-testing, grievances, test notices, and reciprocity. The amendments add a new section relating to the collection and reporting of repair facility data. The amendments add a new section providing requirements for obtaining an emissions compliance certificate where the vehicle is located and being primarily operated outside the affected counties. The amendments eliminate Table A and B relating to the IM240 test. Finally, the amendments update and clarify other provisions in the rule.
- 16) <u>Information and questions regarding these adopted amendments shall be directed to:</u>

Kent E. Mohr Jr., Assistant Counsel Illinois Environmental Protection Agency 1021 North Grand Avenue East

217/782-5544

11

# ENVIRONMENTAL PROTECTION AGENCY

# NOTICE OF ADOPTED AMENDMENTS

P.O. Box 19276 Springfield, Illinois 62794-9276

The full text of the Adopted Amendments begin on the next page:

# NOTICE OF ADOPTED AMENDMENTS

# TITLE 35: ENVIRONMENTAL PROTECTION SUBTITLE B: AIR POLLUTION CHAPTER II: ENVIRONMENTAL PROTECTION AGENCY

# PART 276 PROCEDURES TO BE FOLLOWED IN THE PERFORMANCE OF INSPECTIONS OF MOTOR VEHICLE EMISSIONS

# SUBPART A: GENERAL PROVISIONS

Section	
276.101	Purpose and Applicability
276.102	Definitions
276.103	Abbreviations
276.104	Incorporations by Reference
	SUBPART B: VEHICLE EMISSIONS INSPECTION PROCEDURES
Section	
276.201	General Description of Vehicle Emissions Inspection Procedures
276.202	Pollutants to be Tested – Exhaust Test
276.203	Dilution - Steady-State Idle Exhaust Test-and Transient Loaded Mode Exhaust
	Test
276.204	Steady-State Idle Exhaust Emissions Test Procedures
276.205	Evaporative System Integrity Test Procedures
276.206	Engine and Fuel Type Modifications
276.207	Transient Loaded Mode Exhaust Emissions Test Procedures (Repealed)
276.208	On-Road Remote Sensing Test Procedures
276.209	On-Board Diagnostic Test Procedures
SUBPA	RT C: <u>EMISSIONS COMPLIANCE</u> STICKER OR CERTIFICATE ISSUANCE, <u>DISPLAY</u> , AND POSSESSION
Section	

Section	
276.301	General Requirements
276.302	Determination of Affected Counties
276.303	Emissions Compliance Inspection Sticker or Certificate Design and Content
276.304	Initial Emissions Inspection Stickers or Certificates (Repealed)

# NOTICE OF ADOPTED AMENDMENTS

276.305	Exempt Emissions Inspection Stickers or Certificates (Repealed)
276.306	Renewal Emissions Inspection Stickers or Certificates (Repealed)
276.307	Temporary Emissions Inspection Stickers or Certificates (Repealed)
276.308	Corrected or Interim Emissions Inspection Stickers or Certificates (Repealed)
276.309	Waiver Emissions Inspection Stickers or Certificates (Repealed)
276.310	Emissions Inspection Sticker and Certificate Display and Possession (Repealed)
276.311	Change of Assigned Test Month (Repealed)
276.312	Economic Hardship Extension Stickers or Certificates (Repealed)

# SUBPART D: WAIVER, AND ECONOMIC HARDSHIP EXTENSION, AND OUTSIDE OF AFFECTED COUNTIES ANNUAL EXEMPTION REQUIREMENTS

Secti	on	
276.4	401	Waiver Requirements
276.4	402	Low Emissions Tuneups (Repealed)
276.4	403	Denial or Issuance of Waiver
276.4	404	Economic Hardship Extension Requirements
276.4	<u>405</u>	Outside of Affected Counties Annual Exemption Requirements

# SUBPART E: TEST EQUIPMENT SPECIFICATIONS

	Section	
	276.501	General Requirements
	276.502	Steady-State Idle Exhaust Test Analysis Systems Functional Requirements
	276.503	Steady-State Idle Exhaust Test Analysis Systems Performance Criteria
	276.504	Evaporative System Integrity Test Functional Requirements and Performance
		Criteria
	276.505	Transient Loaded Mode Test Systems Functional Requirements (Repealed)
	276.506	Transient Loaded Mode Test Systems Performance Criteria (Repealed)
•	276.507	On-Road Remote Sensing Test Systems Functional Requirements and
		Performance Criteria
	276.508	On-Board Diagnostic Test Systems Functional Requirements and Performance
		Criteria

# SUBPART F: EQUIPMENT MAINTENANCE AND CALIBRATION

Section	
276.601	Steady-State Idle Test Equipment Maintenance

# NOTICE OF ADOPTED AMENDMENTS

276.602	Steady-State Idle Test Equipment Calibration
276.603	Evaporative System Integrity Test Maintenance and Calibration
276.604	Record Keeping
276.605	Transient Loaded Mode Test Equipment Maintenance and Calibration (Repealed)
276.606	On-Road Remote Sensing Test Systems Maintenance and Calibration
276.607	On-Board Diagnostic Test Systems Maintenance and Calibration
	SUBPART G: FLEET <u>SELF TESTING</u> REQUIREMENTS
Section	
276.701	General Requirements
276.702	Fleet Inspection Permit
276.703	Fleet Inspection Permittee Operating Requirements
276.704	Private Official Inspection Station Auditing and Surveillance
276.705	Fleet Station Auditing and Surveillance (Renumbered)
	SUBPART H: GRIEVANCE PROCEDURE
Section	
276.801	General Requirements
276.802	Procedure for Filing Grievance
276.803	Agency Investigation
276.804	Review of Agency's Determination
	SUBPART I: NOTICES
Section	
276.901	General Requirements
276.902	VehicleInitial Emissions TestInspection Notice
276.903	Warning Notice (Repealed)
276.904	Second Warning Notice (Repealed)
	SUBPART J: RECIPROCITY WITH OTHER JURISDICTIONS
Section	
276.1001	Ι
	Jurisdictions Requiring Vehicle Emissions Inspection
276.1002	Requirements for Vehicles Registered in Other Jurisdictions Requiring Vehicle

# NOTICE OF ADOPTED AMENDMENTS

Emissions Inspection and Located in an Affected County

### SUBPART K: REPAIR FACILITY PERFORMANCE REPORTING

276.1101 Requirements for Collecting and Reporting Data Pertaining to the Repair of Vehicles that Failed or Were Rejected from an Emissions Inspection

276.TABLE A

276.TABLE B

Fast-Pass Speed Variation Limits Using Positive Kinetic Energy (PKE)

Measurements (Repealed)

AUTHORITY: Implementing the Vehicle Emissions Inspection Law of 2005 [625 ILCS 5/13C] and authorized by Sections 13C-10 and 13C-20 of the Vehicle Emissions Inspection Law of 2005 [625 ILCS 5/13C-10 and 13C-20].

SOURCE: Adopted at 10 III. Reg. 13954, effective August 13, 1986; amended at 16 III. Reg. 10230, effective June 15, 1992; amended at 20 III. Reg. 8456, effective June 14, 1996; amended at 22 III. Reg. 18867, effective September 28, 1998; amended at 26 III. Reg. 8113, effective May 17, 2002; amended at 35 III. Reg. 11268, effective June 28, 2011.

#### SUBPART A: GENERAL PROVISIONS

# Section 276.101 Purpose and Applicability

- a) Purpose
  - This Part establishes specific requirements and procedures to be followed in complying with the motor vehicle emissions inspection requirement and specific requirements and specific-procedures to be followed in the performance of inspections of motor vehicle emissions.
- b) Applicability
  The provisions of this Part apply tonecessary for the implementation of the Enhanced I/M testing program mandated by the Vehicle Emissions Inspection Law of 20051995 shall be implemented upon initiation of the Enhanced I/M testing program, scheduled to begin December 1, 1998.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

# NOTICE OF ADOPTED AMENDMENTS

#### Section 276.102 Definitions

- a) Except as hereinafter stated and unless a different meaning of a term is clear from its context, the definitions of terms used in this Part shall be the same as those used in the Environmental Protection Act [415 ILCS 5] and the Vehicle Emissions Inspection Law of 20051995 [625 ILCS 5/Ch.13CB].
- b) The following definitions apply to this Part:

"Accuracy" means the combination of bias and precision errors, technically defined as uncertainty, that quantifies the differences between a measured and true value.

"Adjusted loaded vehicle weight (ALVW)" means the vehicle curb weight plus the gross vehicle weight rating divided by two.

"Affected county" means any county or portion thereof, as defined in Section 13CB-5 of the Vehicle Emissions Inspection Law of 20051995.

"Agency" means the Illinois Environmental Protection Agency or its designee.

"Assigned test month" means the month and year allocated by the Agency for testing a vehicle. The first day of the Assigned Test Month shall be 4 months prior to the sticker or certificate Expiration Date.

"Calibration gas" means a gas of known concentration used to establish the response curve of the exhaust gas analyzer.

"Corrected or interim emissions inspection sticker or certificate" means a sticker or certificate issued in accordance with Section 276.308 of this Part that contains a reassigned vehicle test month issued to the owner(s) of a vehicle subject to emissions inspection who has petitioned the Agency for a change in Assigned Test Month, and whose vehicle has previously been issued an Initial Emissions Inspection Sticker or Certificate with an Assigned Test Month.

"Diagnostic trouble code (DTC)" means an alphanumeric code that is set

# NOTICE OF ADOPTED AMENDMENTS

in a vehicle's onboard computer when a monitor detects a condition likely to indicate the existence of an emission related malfunction of the vehicle.

"Drift" means the amount of change in analyzer reading over a period of time. Zero drift refers to the change of zero reading. Span drift refers to a change in the reading at a specified span gas calibration point.

"Economic hardship extension" means a time extension of one year extension to the test-by date that may be granted to the ownersowner(s) of a vehicle in order for the ownersowner(s) to comply with the requirements of the Vehicle Emissions Inspection Law of 20051995.

"Emissions compliance certificate" means a certificate issued to an owner of a vehicle registered in an affected county who successfully complies with the Vehicle Emissions Inspection Law of 2005 and the requirements of this Part. As required by the context, this means an emissions compliance certificate, annual exemption certificate or emissions inspection certificate.

"Emission control devices" means those components of a vehicle that which were designed and are used to control vehicle exhaust and evaporative system emissions. For the purpose of this Part, this term refers to components with which the vehicle was originally equipped or direct replacements.

"Equivalent test weight" means the loaded vehicle weight for light duty vehicles and light duty trucks 1, and the adjusted loaded vehicle weight for light duty trucks 2 and heavy duty trucks.

"Evaporative system integrity test" means a test of the fuel cap portion of a vehicle's evaporative system, which consists of either a fuel cap leak flow test, a fuel cap pressure decay test, or a fuel cap visual functional test, as applicable.

"Exempt emissions inspection sticker or certificate" means a sticker or certificate issued in accordance with Section 276.305 of this Part to the owner(s) of a vehicle registered in an Affected County which is exempt from emissions inspection pursuant to Section 13B-15(f) or 13B-15(g) of

# NOTICE OF ADOPTED AMENDMENTS

the Vehicle Emissions Inspection Law of 1995, and the requirements of this Part.

"Exhaust gas analyzer" means a device that has the capability to identify unknown concentrations of particular constituents in motor vehicle exhaust gases by comparison with known concentrations of analytical gases.

"Expiration date" means the deadline for having a vehicle inspected and obtaining the appropriate sticker or certificate.

"Fleet inspection permit" means a permit issued to fleet self-testers in accordance with Subpart G.

"Fleet inventory" means those vehicles <u>thatwhich</u> have been registered with the Agency for the purpose of fleet self-testing and <u>thatwhich</u> have been assigned a test <u>eligibility datementh</u>.

"Fleet vehicle" means any non-exempt vehicle registered with the Agency for the purpose of fleet self-testing.

"Fuel cap" means a device used to seal a vehicle's fuel inlet.

"Fuel cap leak flow test" means a test performed in accordance with this Part on a vehicle's fuel cap using a fuel cap leak flow tester to determine whether the vehicle complies with the evaporative system emission standards of 35 Ill. Adm. Code 240.

"Fuel cap leak flow tester" (fuel cap tester) or "fuel cap tester" means a device used to determine the leak flow integrity of a vehicle's fuel cap by comparing the measured leak flow of the fuel cap with an established fuel cap leak flow standard.

"Fuel cap pressure decay test" means the test performed in accordance with this Part on a vehicle's fuel cap using a fuel cap pressure decay tester to determine whether the vehicle complies with the evaporative system emission standards of 35 Ill. Adm. Code 240.

#### NOTICE OF ADOPTED AMENDMENTS

"Fuel cap pressure decay tester" means a device used to determine the pressure decay integrity of a vehicle's fuel cap by monitoring the pressure behind the fuel cap for a 10 second period and comparing the measured pressure decay of the fuel cap to an established fuel cap pressure decay standard.

"Fuel cap visual functional test" means the test performed in accordance with this Part on a vehicle's fuel cap using visual analysis to determine whether the vehicle complies with the evaporative system emission standards of 35 Ill. Adm. Code 240.

"Full-service official inspection station" means an inspection station that offers the full range of emissions inspection services and customer service functions, including waiver inspections.

"Gross vehicle weight rating (GVWR)" means the value specified by the manufacturer as the maximum design loaded weight of a single vehicle.

"HC hangup" means hydrocarbons <u>thatwhich</u> cling to the surface of the analyzer gas sampling stream causing errors in hydrocarbon readings.

"Heavy duty vehicle (HDV)" means a motor vehicle rated at more than 8500 pounds GVWR or that has a vehicle curb weight of more than 6000 pounds or that has a basic vehicle frontal area in excess of 45 square feet.

"High idle" means a vehicle operating condition with engine disconnected from an external load (placed in either neutral or park) and operating at a speed of  $2500 \pm 300$  RPM.

"Household income" means the gross income of all household members, except wage or salary income earned by dependent minors under 18 years of age. A head of household and his or her spouse are not considered as minors. Gross income includes wages, interest, annuities, pensions, social security, retirement, disability, public aid, alimony, child support, unemployment benefits, workers' compensation, and any other indirect income such as utility allowances.

"Idle mode" means that portion of a vehicle emission test procedure

 $\Pi$ 

### ENVIRONMENTAL PROTECTION AGENCY

#### NOTICE OF ADOPTED AMENDMENTS

conducted with the engine disconnected from an external load and operating at minimum throttle.

"Initial emissions inspection sticker or certificate" means a sticker or certificate issued in accordance with Section 276.304 of this Part to the owner(s) of a vehicle that has not been tested because such vehicle was not previously subject to inspection, but has become subject to inspection in accordance with the Vehicle Emissions Inspection Law of 1995.

"Initial idle mode" means the first of up to two idle mode sampling periods during a steady-state idle mode test, during which exhaust emission measurements are made with the vehicle in "as-received" condition.

"Interference" means those exhaust gas analyzer read-out errors caused by instrument response to non-interest gases typically occurring in vehicle exhaust.

"Light duty truck I (LDT1)" means a motor vehicle rated at 6,000 pounds maximum GVWR or less and which has a vehicle frontal area of 45 square feet or less, and which is designed primarily for purposes of transportation of property or is a derivation of such a vehicle, or is designed primarily for transportation of persons and has a capacity of more than 12 persons, or is available with special features enabling off street or off-highway operation and use.

"Light duty truck 2 (LDT2)" means a motor vehicle rated between 6,001 and 8,500 pounds maximum GVWR and which has a vehicle frontal area of 45 square feet or less, and which is designed primarily for purposes of transportation of property or is a derivation of such a vehicle, or is designed primarily for transportation of persons and has a capacity of more than 12 persons, or is available with special features enabling off-street or off-highway operation and use.

"Light duty vehicle (LDV)" means a passenger car or passenger ear derivative capable of seating 12 passengers or fewer.

"Loaded vehicle weight" means the vehicle curb weight plus 300 pounds.

11

# **ENVIRONMENTAL PROTECTION AGENCY**

# NOTICE OF ADOPTED AMENDMENTS

"Low income" means the household income during the preceding 12 month period was not more than 150 percent of the latest available poverty guidelines established by the U.S. Department of Health and Human Services for the contiguous United States and the District of Columbia.

"Malfunction indicator light (MIL)" or "MIL" means the light found on the dashboard of OBD-equipped vehicles that is required to be illuminated when the OBD system detects malfunctions likely to result in emissions exceeding applicable emission standards. The MIL must display the phrase "Check Engine" or "Service Engine Soon". The word "Powertrain" may be substituted for "Engine". Alternatively, the ISO engine symbol may be substituted.

"National Institute of Standards and Technology(NIST) gas" or "NIST gas" means a standard gas maintained or made available by the National Institute of Standards and Technology for the purpose of determining the accuracy of calibration gases.

"Non-exempt vehicle" means any vehicle subject to emission inspections, regardless of whether the vehicle is in a certified configuration, under the Vehicle Emissions Inspection Law of 20051995.

"Non-fleet vehicle" means any non-exempt vehicle except for vehicles registered with the Agency for the purpose of fleet self-testing.

"Official inspection station" means a vehicle emission inspection facility operated by the Agency or the Agency's Contractor for the purpose of conducting emission inspections on non-fleet vehicles.

"On board diagnostic data link connector (DLC)" means the interface between a vehicle's OBD system and the OBD scan equipment.

"On-board diagnostic readiness code" means a status flag stored by a vehicle's onboard computer that indicates whether a given monitor has been run (i.e., whether the component or system in question has been checked to determine if it is functioning properly).

# NOTICE OF ADOPTED AMENDMENTS

"On-board diagnostic (OBD) system" means equipment designed to monitor the performance of emission control equipment, fuel metering systems, ignition systems and other equipment and operating parameters for the purpose of detecting malfunctions or deterioration in performance that would be expected to cause the vehicle to exceed federal emission standards.

"On-board diagnostic test" means the electronic retrieval of stored readiness status, diagnostic trouble codes, and MIL illumination status from a vehicle's OBD system to determine if any emission related trouble codes are present and if the MIL is commanded to be on, which would indicate the existence of an emission related malfunction with the vehicle.

"On-road remote sensing test" means the observation, measurement, and recording of vehicle exhaust emission concentrations of hydrocarbons (HC), carbon monoxide (CO), and carbon dioxide (CO<sub>2</sub>) present in each in-use vehicle while traveling on roadways or in specified areas by equipment that is not connected to the vehicle.

"Preconditioning mode" means a period of steady-state <del>loaded mode or</del> high-idle operation conducted to ensure that the engine and emissions control system components are operating at normal operating temperatures, thus minimizing false failure caused by improper or insufficient warm-up.

"Private official inspection station" means a vehicle emission inspection facility operated by a registered owner or lessee of 15 or more non-exempt fleet vehicles.

"Recognized repair technician" means a person professionally engaged in vehicle repair, employed by a going concern whose purpose is vehicle repair, or possessing nationally recognized certification for emission related diagnosis and repair.

"Renewal emissions inspection sticker or certificate" means a sticker or certificate issued in accordance with Section 276.306 of this Part to an owner of a vehicle which successfully passes a vehicle emissions test in accordance with the provisions of this Part.

#### NOTICE OF ADOPTED AMENDMENTS

"Second-chance idle mode" means the second of two idle mode sampling periods during a steady-state idle mode test, preceded by a preconditioning mode and utilized as a second chance to pass idle exhaust emission standards immediately following an initial idle mode failure.

"Span gas" means a gas of known concentrations <u>thatwhich</u> is used to check or adjust the analyzer response characteristics to those determined by the calibration gases.

"Steady-state idle test" means a vehicle emission test procedure consisting of an initial idle mode measurement of exhaust emissions followed, if necessary, by a loaded or high idle preconditioning mode and a second-chance idle mode.

"Temporary emissions inspection sticker or certificate" means a sticker or certificate issued in accordance with Section 276.307 of this Part to an owner of a vehicle subject to inspection which currently has a valid initial or renewal emission inspection sticker or certificate, and which has met the requirements of this Part.

"Test-by date" or "TBD" means the date by which the vehicle is due to have an emissions inspection and corresponds to the date the vehicle's registration will expire. For non-expiring vehicle registrations, the TBD is the date of the vehicle's purchase anniversary month or, if not available, the month the vehicle was added to the Illinois Secretary of State's registration database.

"Test cycle" means the two-year period between a vehicle's <u>test eligibility</u> dates Assigned Test Months.

"Test eligibility date" or "TED" means the first day of the third month prior to the vehicle's TBD.

"Vehicle curb weight" means the actual vehicle weight plus standard equipment and a full fuel tank.

"Vehicle emissions test notice" means a notice sent by the Agency to the

# NOTICE OF ADOPTED AMENDMENTS

owners of a vehicle informing the owners of the need to comply with the requirements of the Vehicle Emissions Inspection Law of 2005.

"Vehicle inspection report" means a report issued to the motorist indicating the results of an emission inspection or waiver determination.

"Visual functional test" means a visual examination of a vehicle's fuel cap for any readily apparent wear, tampering, or defects that which would prevent the fuel cap from operating properly.

"Waiver" means a suspension of the requirement that a non-exempt vehicle comply with <u>testexhaust emission</u> standards after two or more attempts to do so, as provided for in this Part.

"Waiver emissions inspection sticker or certificate" means a sticker or certificate issued in accordance with Section 276.309 of this Part to the owner(s) of a vehicle which has failed a vehicle emissions test and at least one retest, but successfully complies with the applicable waiver requirements of this Part.

"Waiver inspection" means an inspection conducted by a waiver inspector to determine waiver eligibility.

"Waiver inspector" means a person authorized by the Agency to conduct waiver inspections and to approve or disapprove applications for a waiver.

"Waiver inspection report" means a form containing waiver eligibility requirements which is completed by a waiver inspector to determine whether a vehicle is eligible for a waiver.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

#### Section 276.103 Abbreviations

Abbreviations used in this Part include the following:

ALVW cc/min

adjusted loaded vehicle weight cubic centimeters per minute

# NOTICE OF ADOPTED AMENDMENTS

CO	carbon monoxide
$CO_2$	carbon dioxide
CFV	critical flow venturi
CVS	<del>constant volume sampler</del>
DLC	<del>data link connector</del>
DTC	diagnostic trouble code
<del>gpm</del>	<del>grams per mile</del>
GVWR	gross-vehicle weight rating
HC	hydrocarbons, as hexane
HDV	heavy duty vehicle
<del>lar</del>	<del>hour</del>
I/M	inspection and maintenance
₩	kilowatt
LDT1	light duty truck-l
LDT2	light duty truck 2
LDV	light duty vehicle
LVW	loaded-vehicle-weight
<del>mi</del>	mile, miles
MIL	malfunction indicator light
NDIR	non dispersive infrared
NIST	National Institute for Standards and Technology
NO	nitrogen oxide
$NO_x$	oxides of nitrogen
$NO_2$	n <del>itrogen dioxide</del>
OBD	on-board diagnostics
ppm	parts per million by volume
<del>ppmC</del>	parts-per-million, carbon
<del>psi</del>	<del>pounds per square inch</del>
RPM	revolutions per minute
SDM	source detector module
TBD	test-by date
TED	test eligibility date

vehicle identification number standard error of estimate

subsonic venturi

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

SE

SSV

# NOTICE OF ADOPTED AMENDMENTS

# Section 276.104 Incorporations by Reference

The following materials are incorporated by reference and include no later editions or amendments:

- a) 40 CFR 85.2225 (July 1, 1994). United States Environmental Protection Agency (USEPA), "IM240 and Evaporative Test Guidance: 1998 Revised Technical Guidance," Report EPA AA-RSPD-IM-98-1 (Draft), 2565 Plymouth Road, Ann Arbor MI 48105 (March 1998).
  - NOTE: Sections of this Guidance are referenced as though they are sections of 40 CFR-85.
- b) United States Environmental Protection Agency (USEPA), "High Tech I/M Test Procedures, Emission Standards, Quality Control Requirements, and Equipment Specifications: IM240 and Functional Evaporative System Tests, Revised Technical Guidance," Report EPA-AA-RSPD-IM-96-1 (Draft), 2565 Plymouth Road, Ann Arbor MI-48105 (June 1996).
  - NOTE: Sections of this Guidance are referenced as though they are sections of 40 CFR 85.
- be) 40 CFR 85.2222, 85.2223, and 85.2231 (July 1, 2001).
- d) 40 CFR 51.353(e), 51.358(b) and Appendix D to Subpart S (July 1, 2001).

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

SUBPART B: VEHICLE EMISSIONS INSPECTION PROCEDURES

# Section 276.201 General Description of Vehicle Emissions Inspection Procedures

Compliance with steady-state idlevehicle exhaust, evaporative system integrityemissions, OBD on-board diagnosties, and on-road sensing test standards contained in 35 III. Adm. Code 240 shall be determined by use of test procedures and other requirements as applicable, as set forth in this Part, and shall be performed to the extent practicable. The test procedure applicable to each non-exempt vehicle shall be based on the model year and vehicle type as supplied by the manufacturer. If this information is not available from the manufacturer, the model year and

#### NOTICE OF ADOPTED AMENDMENTS

vehicle type shall be based on registration information as supplied by the Illinois Secretary of State.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

# Section 276.203 Dilution - Steady-State Idle Exhaust Test-and Transient Loaded Mode Exhaust Test

a)Steady-State Idle Exhaust TestTo prevent excess dilution in a steady-state idle exhaust emissions test described in Section 276.204, the sample probe shall be inserted a minimum of 10 inches into the vehicle's tailpipe. Extension boots shall be utilized if it is impossible to insert the sample probe at least 10 inches into the tailpipe. A vehicle emission test shall be invalid if the applicable emission standards contained in 35 Ill. Adm. Code 240 are met but the sum of the CO and CO<sub>2</sub> concentrations in the exhaust gas does not exceed 6 percent during the sample averaging period(s).

#### b) Transient Loaded Mode Exhaust Test

To prevent excess dilution in a transient loaded mode exhaust emissions test described in Section 276.207, the exhaust collection system shall be positioned to insure complete capture of the entire exhaust stream from the tailpipe during the transient driving cycle. The test system shall verify that the entire exhaust stream is being collected through continuous monitoring of exhaust CO<sub>2</sub> generated during the transient driving cycle and comparison with theoretical levels of exhaust CO<sub>2</sub> produced by the vehicle being tested. A vehicle emission test shall be invalid if the measured values fall below expected values during the transient driving cycle. At a minimum, the emission test shall be invalid if five consecutive one second average CO<sub>2</sub> values fall below 0.085 percent during seconds 5 through 220 of the transient driving cycle.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

# Section 276.204 Steady-State Idle Exhaust Emissions Test Procedures

a) Steady-State Idle Test

1)Test Description The steady-state idle test with loaded preconditioning may be substituted for the OBD test transient loaded mode exhaust gas analysis for those vehicles identified in Section 13CB-25(e) and(d) of the Vehicle Emissions

# NOTICE OF ADOPTED AMENDMENTS

Inspection Law of 20051995. The steady-state idle test with loaded preconditioning consists of a first-chance idle mode test followed, if necessary, by a second-chance test. The second-chance test consists of a loaded preconditioned mode using a dynamometer, or a high idle preconditioned mode while in neutral or park, followed immediately by an idle mode.

# 2) Engine Re-Start

In addition to the test procedures of this Section, the engines of 1981–1987 model year Ford Motor Company vehicles and 1984–1985 model year Honda Preludes must be shut off for not more than 10 seconds and restarted prior to initiating the idle mode of the second-chance test. The probe shall be removed from the tailpipe or the sample pump turned off if necessary to reduce analyzer fouling during the restart procedure.

# b) General Requirements

- 1) Initial tests (i.e., those occurring for the first time in a vehicle's scheduled test cycle) shall be performed without repair or adjustment at the inspection facility prior to the test.
- 2) Tests shall be performed with Agency-approved equipment that has been calibrated according to the quality procedures contained in Section 276.602 of this Part.
- 3) Vehicles with apparent leaks of fuel, oil, coolant, or exhaust shall not be tested.
- 4) Vehicles with missing tail pipe sections that which would prohibit full insertion of an analyzer probe shall not be tested.
- Vehicles shall be tested with their engines and emissions control systems at normal operating temperatures and not overheating (as indicated by gauge, temperature lamp, touch test on the radiator hose, and/or boiling radiator).
- 6) Vehicles shall be tested without any accessories in operation.

# NOTICE OF ADOPTED AMENDMENTS

- 7) Vehicles must be operated during each mode of the test with the gear selector in the position described as follows: A) in drive for automatic transmissions and in second (or third if more appropriate) for manual transmissions for the loaded preconditioning mode; and B) in neutral or park for the idle mode test and the high idle preconditioning mode.
- 8) For vehicles with multiple tailpipes, separate test results from each tailpipe shall be numerically averaged for each pollutant sampled unless equipment capable of simultaneously sampling multiple tailpipes is utilized.
- 9) Vehicles subject to loaded mode preconditioning under subsection (e)(2)(B)(i) of this Section shall be rejected from testing if drive axle tires:
  - A) exhibit visible cords, belts, bubbles, cuts, or other damage, or
  - B) are space-saver spare tires, or
  - C) are not reasonably sized.
- Vehicles subject to loaded mode preconditioning under subsection (e)(2)(B)(i) of this Section shall have their drive axle tires inspected for proper inflation. If the air pressure of one or more of these tires appears low, it shall be inflated to approximately 30 psi, or to tire sidewall pressure, or manufacturer's recommendations.

# c) Procedures

- 1) The analysis of exhaust gas concentrations must begin 10 seconds after the applicable test mode begins.
- 2) Exhaust gas concentrations must be analyzed at a minimum rate of once every 0.75 second.
- 3) The measured value for the pass/fail determination shall be a simple running average of the measurements taken over 5 seconds.
- 4) When used for leaded mode preconditioning, the dynamometer must be

## NOTICE OF ADOPTED AMENDMENTS

warmed up, in stabilized operating condition, adjusted, and ealibrated in accordance with the procedures contained in Section 276.603 of this Part. Prior to each test, variable curve dynamometers must be checked for proper setting of the road load indicator or road load controller.

- With the exception of those vehicles specified in <u>subsection</u> subsections (c)(56) and (c)(7) of this Section, the tachometer must be attached to the vehicle in accordance with the analyzer manufacturer's instructions.
- Vehicles that cannot continuously meet the engine speed requirements of subsection (e)(1)(B) of this Section within 30 seconds after initiation of the first-chance test shall be rejected upon verification of the proper operation and placement of the tachometer. If it is determined that the operation or placement of the tachometer is faulty, immediate corrective action shall be taken and the vehicle shall be retested in accordance with subsection (e) of this Section.
- 7) For 1996 and newer model year LDVs, LDT1s, and LDT2s, the OBD data link connector shall be used to monitor RPM. In the event that an OBD data link connector is not available or that an RPM signal is not available over the data link connector, a tachometer shall be used instead.
- If the engine or vehicle speed, as applicable, falls outside the limits specified in <u>subsectionsubsections</u> (e)(1)(B), (e)(2)(B)(i), (e)(2)(B)(ii) or (e)(2)(C) of this Section, as applicable, for more than 5 seconds in any one excursion, or 15 seconds over all excursions within a test mode, the mode timer shall be reset to zero and the mode restarted.
- For vehicles whose design prevents the monitoring of the engine rpm rate with a tachometer, the engine speed requirements of subsections (e)(1)(B), (e)(2)(B), and (e)(2)(C) of this Section shall not apply. The preconditioning mode of a second-chance idle test shall consist of accelerating the vehicle's engine to an estimated rate of 2500 rpm for a period of 30 seconds prior to initiating a second-chance idle mode test.
- The sample probe must be inserted into the vehicle's tailpipe to a minimum depth of 10 inches. If the vehicle's exhaust system prevents insertion to this depth, a tailpipe extension must be used.

## NOTICE OF ADOPTED AMENDMENTS

- The measured concentration of CO plus CO<sub>2</sub> must be greater than or equal to 6 percent or the vehicle will be rejected.
- 1012) If a vehicle's engine stalls at any time during the test sequence, the test shall be aborted and restarted. If after 3 attempts the test cannot be completed, the vehicle shall be rejected.

#### d) Pass/Fail Determination

A pass or fail determination is made for each applicable test mode based on a comparison of the test standards contained in 35 Ill. Adm. Code 240.I52 with the measured value for HC and CO as described in subsection (c) of this Section. A vehicle passes the test mode if any pair of simultaneous measured values for HC and CO are below or equal to the applicable test standards. A vehicle fails the test mode if the values for either HC or CO, or both, in all simultaneous pairs of values are above applicable standards.

# e) Test Sequence

The steady-state idle test consists of a first-chance test and a second-chance test. The first-chance test consists only of an idle mode. The second-chance test consists of a preconditioning mode followed immediately by an idle mode, and is performed only if the vehicle fails the first-chance test.

- 1) First-Chance Test
  - A) The test starts when the conditions specified in subsections (e)(1)(B) and (e)(1)(C) of this Section are met.
  - B) The mode starts when the vehicle engine speed is between 350 and 1300 rpm. The minimum mode length is determined as described under subsection (e)(1)(C) of this Section.
  - C) The pass/fail analysis begins after an elapsed time of 10 seconds. A pass or fail determination is made for the vehicle and the mode is terminated in accordance with subsections (e)(1)(C)(i) through (e)(1)(C)(iv) of this Section.
    - i) The vehicle passes the idle mode and the test terminates on

#### NOTICE OF ADOPTED AMENDMENTS

or before an elapsed time of 30 seconds, if the measured values are less than or equal to the applicable test standards as described in subsection (d) of this Section.

- ii) The pass/fail analysis shall continue beyond 30 seconds as long as emission readings are declining based upon comparison of the last 5 consecutive measured values. The vehicle passes the idle mode and the test is immediately terminated if, at any point between an elapsed time of 30 seconds and 90 seconds, the measured values are less than or equal to the applicable test standards described in subsection (d) of this Section.
- iii) The vehicle fails the first-chance test if the provisions of subsection (e)(1)(A), (e)(1)(C)(i), or (e)(1)(C)(ii) of this Section are not met.
- iv) The vehicle shall fail the first-chance test and the secondchance test shall be omitted if no measured values less than 1800 ppm HC are found by an elapsed time of 30 seconds.

## 2) Second-Chance Test

- A) If the vehicle fails the first-chance test, a second-chance test is performed except as described in subsection (e)(1)(C)(iv) of this Section.
- B) Preconditioning Mode

At all Official Inspection Stations, and those Private Official Inspection Stations equipped with dynamometers, all LDVs, LDT1s, and LDT2s that require a second chance test shall be preconditioned in accordance with the loaded mode procedures specified in subsection (e)(2)(B)(i) of this Section. All LDVs, LDT1s, LDT2s, and HDVs that, because of the vehicle design or configuration, cannot be preconditioned on the dynamometer, or are tested at Private Official Inspection Stations not equipped with dynamometers, shall be preconditioned using the high idle

#### ENVIRONMENTAL PROTECTION AGENCY

## NOTICE OF ADOPTED AMENDMENTS

preconditioning procedures specified in subsection (e)(2)(B)(ii) of this Section.

## i) Loaded Preconditioning Mode

The mode starts when the dynamometer speed is within the limits specified for the vehicle engine size in accordance with the following schedule. The mode continues for an elapsed time of 30 seconds.

# Dynamometer Test Schedule

	Roll Speed	Brake
	Mph	<del>Horsepower</del>
Number of Cylinders	<u>(km/hr)</u>	$\frac{(kW)}{(kW)}$
4 or less	22-25	2.8-4.1
	<del>(35-40)</del>	(2.1-3.1)
5 to 6	<del>29-32</del>	6.8-8.4
	<del>(47-52)</del>	(5.1-6.3)
<del>7 or more</del>	32-35	8.4-10.8
	( <del>52-56)</del>	(6.3-8.1)

# ii) High Idle Preconditioning Mode

The <u>high idle preconditioning</u> mode starts when the engine speed is between 2200 and 2800 rpm, or between 1650 and 1950 rpm on specified vehicles equipped with ZF 4-speed Automatic Transmissions. The mode continues for an elapsed time of 30 seconds.

## C) 1dle Mode

The mode starts 5 seconds after the dynamometer speed has reached zero if loaded preconditioning has been used, or when the vehicle engine speed returns to be between 350 and 1300 rpm after high idle preconditioning is used. The minimum idle mode length is determined as described in subsection (e)(2)(D) of this Section.

## NOTICE OF ADOPTED AMENDMENTS

- D) The pass/fail analysis begins after an elapsed time of 10 seconds. A pass or fail determination is made for the vehicle and the idle mode is terminated in accordance with the following:
  - i) Thethe vehicle passes the idle test and the test terminates on or before an elapsed time of 60 seconds if the measured values are less than or equal to the applicable test standards as determined by the procedure described in subsection (d) of this Section;
  - ii) The the vehicle fails the idle test and the test terminates if the provisions of subsection (e)(2)(D)(i) are not met within an elapsed time of 60 seconds.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

# Section 276.205 Evaporative System Integrity Test Procedures

a) Applicability

The evaporative system integrity test shall be performed in accordance with the fuel cap leak flow test procedures or fuel cap pressure decay test procedures, and fuel cap visual functional test procedures specified in subsections (b) and (c) of this Section.

## b) Test Procedures

The fuel cap shall be removed from the vehicle's fuel inlet and installed on the fuel cap leak flow tester, using an adapter if necessary. All fuel caps that require a key for removal from the vehicle's fuel inlet shall be tested with the key removed from the lock. The workstationAt-Official Inspection Stations, the lane computer shall provide the inspectorlane operator with information as to whether the fuel cap tester can be used to test the vehicle's fuel cap and which adapter, if any, is required, based on one or more of the following items: vehicle identification number (VIN), make, model, and model year. If the fuel cap can be tested, then the following task shall be performed:

П

#### ENVIRONMENTAL PROTECTION AGENCY

## NOTICE OF ADOPTED AMENDMENTS

- A) The the fuel cap leak flow tester shall be pressurized to 30 ±1 inches of water. The inspector shall initiate the test. The fuel cap leak flow tester shall measure the fuel cap leak flow rate and simultaneously compare this flow rate with the flow rate through the calibrated orifice;
- B) Withinwithin 15 seconds after the depression of the start-test button, the fuel cap leak flow tester shall make a pass/fail determination. Pass/fail analysis shall be determined according to the procedures in subsection (c) of this Section;
- C) <u>Fuelfuel</u> caps <u>thatwhich</u> have failed an initial integrity test under subsection (c)(4) of this Section shall immediately receive a second-chance fuel cap leak flow test after first ensuring that the fuel cap has been installed on the fuel cap leak flow tester correctly. The procedure contained in subsections (b)(1)(A) and (b)(1)(B) of this Section shall be repeated; and
- D) At the conclusion of all fuel cap leak flow tests, the fuel cap shall be removed from the fuel cap leak flow tester and replaced on the filler neck, ensuring that it is properly tightened.
- The fuel cap shall be removed from the vehicle's fuel inlet and installed on the fuel cap pressure decay tester, using an adapter if necessary. All fuel caps that require a key for removal from the vehicle's fuel inlet shall be tested with the key removed from the lock. The workstation At Official Inspection Stations, the lane computer shall provide the inspectorlane operator with information as to whether the pressure decay tester can be used to test the vehicle's fuel cap and which adapter, if any, is required, based on one or more of the following items: VIN, make, model, and model year. If the fuel cap can be tested, then the following task shall be performed:
  - A) The the pressure decay tester shall be pressurized to 28 ±1 inches of water. The inspector shall initiate the test. The pressure decay tester shall monitor the pressure behind the fuel cap and look for pressure decay;

## NOTICE OF ADOPTED AMENDMENTS

- B) The the pressure decay shall be monitored for 10 seconds after stability is achieved for 10 seconds. Pass/fail analysis shall be determined according to the procedures in subsection (c) of this Section;
- C) <u>Fuelfuel</u> caps that have failed an initial integrity test under subsection (c)(4) of this Section shall immediately receive a second-chance fuel cap pressure decay test after first ensuring that the fuel cap has been installed on the pressure decay tester correctly. The procedure contained in subsections (b)(2)(A) and (b)(2)(B) of this Section shall be repeated; and
- D) Atat the conclusion of all fuel cap pressure decay tests, the fuel cap shall be removed from the pressure decay tester and replaced on the filler neck, ensuring that it is properly tightened.
- 3) Visual Functional Test
  If the vehicle has a fuel cap, but the fuel cap cannot be tested using the leak flow or pressure decay test procedures, then a visual functional test of the fuel cap shall be performed.

#### c) Pass/Fail Determination

- 1) Vehicles which are presented for testing with missing, inaccessible, incorrect, non-removable, illegal, or otherwise non-testable fuel caps shall fail the evaporative system integrity test.
- 2) If the vehicle's fuel cap is present and can be tested using either the fuel cap leak flow test or the fuel cap pressure decay test under subsection (b)(1) or (b)(2) of this Section and, if tested, the test result does not exceed either the fuel cap leak flow rate standard contained in 35 Ill. Adm. Code 240.172(b) or the fuel cap pressure decay standard contained in 35 Ill. Adm. Code 240.172(a), then the vehicle shall pass the evaporative system integrity test.
- 3) If the vehicle's fuel cap is present and is tested under the provisions of subsection (b)(3) of this Section, and the test result does not exceed the

# NOTICE OF ADOPTED AMENDMENTS

visual functional test standard contained in 35 Ill. Adm. Code 240.172(c), then the vehicle shall pass the evaporative system integrity test.

4) If the vehicle's fuel cap is tested using either the fuel cap leak flow test or the fuel cap pressure decay test under the provisions of subsection (b)(1) or (b)(2) of this Section, and does not meet the applicable standards contained in 35 Ill. Adm. Code 240.172, the vehicle shall fail the evaporative system integrity test.

(AGENCY NOTE: No vehicle will be failed under subsection (c) until applicable standards have been adopted at 35 III. Adm. Code 240 and are effective.)

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

## Section 276.207 Transient Loaded Mode Exhaust Emissions Test Procedures (Repealed)

# a) General Requirements

- The test shall consist of up to 240 seconds of mass emission measurement using a constant volume sampler while the vehicle is driven through a computer-monitored driving cycle on a dynamometer with inertia weight settings appropriate for the weight of the vehicle. The driving cycle shall include acceleration, deceleration, and idle operating modes as specified in subsection (e)(1) of this Section. The 240 second sequence may be ended earlier using fast pass algorithms.
- 2) The emission standards and dynamometer inertia and power absorption settings shall be automatically selected for the vehicle being tested based upon the identification and validation of the following, as needed:
  - A) Vehicle type: LDV, LDT1, LDT2, and others as needed;
  - B) GVWR:
  - C) Chassis model year;
  - D) Make;

#### 1.(11(01(1.121.11))

- NOTICE OF ADOPTED AMENDMENTS
- E) Model:
- F) Number of cylinders;
- G) Transmission type;
- H) LVW or ALVW; and
- Engine displacement.

Alternative computerized methods of selecting dynamometer test conditions, such as VIN decoding, may be used.

- 3) The ambient temperature, absolute humidity, and barometric pressure shall be recorded continuously during the transient test, or as a single set of readings if taken less than 4 minutes prior to the transient driving cycle.
- 4) If the vehicle is shut off, the vehicle shall be restarted as soon as possible before the test and shall be running for at least 30 seconds prior to the transient driving cycle begins.
- 5) If a vehicle stalls during a transient test, the test shall be aborted and restarted. If after 3 attempts the test cannot be completed, the vehicle shall be rejected.
- b) Pre-inspection and Preparation
  - 1) Initial tests (i.e., those occurring for the first time in a vehicle's scheduled test cycle) shall be performed without repair or adjustment at the inspection facility prior to the test.
  - 2) A test, once initiated, shall be performed in its entirety regardless of intermediate outcomes, except in the case of invalid test conditions or unsafe conditions.
  - 3) Tests involving measurement shall be performed with Agency approved equipment that is operated in accordance with the procedures contained in 40 CFR 85.2234 (Draft), incorporated by reference in Section 276.104(a)

#### NOTICE OF ADOPTED AMENDMENTS

of this Part.

- 4) All accessories (air conditioning, heat, defogger, radio, automatic traction control if switchable, etc.) shall be turned off (if necessary, by the inspector).
- 5) The vehicle shall be inspected for exhaust leaks. Audio assessment while blocking exhaust flow or gas measurement of CO<sub>2</sub> or other gases shall be acceptable. Vehicles with leaking exhaust systems shall be rejected from testing.
- 6) Vehicles with missing tailpipe sections that prohibit placement of the exhaust collection system to capture the entire exhaust stream shall be rejected from testing.
- 7) The vehicle temperature gauge, if equipped and operating, shall be checked to assess temperature. If the temperature gauge indicates that the engine is well below normal operating temperature, the vehicle shall receive a second-chance emission test if it fails the initial test for HC or CO. Vehicles in overheated condition shall be rejected from testing.
- 8) Vehicles shall be rejected from testing if drive axle tires:
  - A) exhibit visible cords, belts, bubbles, cuts, or other damage, or
  - B) are space saver spare tires, or
  - C) are not reasonably sized tires.
- 9) Vehicles' drive axle tires shall be inspected for proper inflation. If one or more of these tires appears low, it shall be inflated to approximately 30 psi, or to tire sidewall pressure, or manufacturer's recommendation.
- Drive axle tires of vehicles subject to additional testing for the purpose of program evaluation under 40 CFR 51.353, incorporated by reference in Section 276.104(d) of this Part, shall have their tires inflated to tire sidewall pressure.

## NOTICE OF ADOPTED AMENDMENTS

- Background concentrations of HC, CO, NO<sub>x</sub>, and CO<sub>2</sub> shall be sampled as specified in 40 CFR-85.2226(b)(2)(iv) (Draft), incorporated by reference in Section 276.104(a) of this Part, to determine background concentration of dilution air. The sample shall be taken for a minimum of 15 seconds within 120 seconds after the start of the transient driving cycle, using the same analyzers used to measure tailpipe emissions. Average readings over the 15 seconds for each gas shall be recorded in the test record. Testing shall be prevented until the average ambient background levels are less than 20 ppmC HC, 35 ppm CO, and 2 ppm NO<sub>x</sub> (when applicable), or outside ambient air levels (not influenced by station exhaust), whichever are greater.
- While a lane is in operation, the CVS shall continuously purge the CVS hose between tests. The blower may be turned off if the CVS is not in operation, but the system shall be purged for 2 minutes prior to the start of a test if the blower has been turned off. The off time shall be computer monitored and recorded to a history file for quality assurance.
- c) Equipment Positioning and Settings

Vehicle positioning and settings shall be conducted according to the method specified in 40 CFR 85.2221(c) (Draft), incorporated by reference in Section 276.104(a) of this Part, with the following exceptions:

- the cooling fan need only be activated when the ambient temperature exceeds 72°F;
- 2) the parking brake should only be activated on front wheel drive vehicles when possible; and
- 3) the hood will not be opened for cooling purposes.
- d) Vehicle Conditioning
  - Queuing Time

When the measured wait time exceeds 20 minutes, the vehicle shall receive a second-chance emission test if the following conditions apply:

#### NOTICE OF ADOPTED AMENDMENTS

- A) fails the test; and
- B) measured values for HC, CO, and NO<sub>x</sub> (if applicable) are at or below 1.5 times the applicable standards of 35 III. Adm. Code 240.

## 2) Program Evaluation

Vehicles selected for additional testing for the purpose of program evaluation under 40 CFR 51.353, incorporated by reference in Section 276.104(d) of this Part, shall receive two full transient emission tests of 240 seconds each. Results from both tests and the test order shall be separately recorded in the test record. Emission results shall be provided to the motorist according to the following criteria:

- A) If the vehicle passes both tests, then the first test result shall be provided.
- B) If the vehicle passes one test and fails the other test, then the test results from the passing test shall be provided.
- C) If the vehicle fails both tests, then the test results from the second test shall be provided.

# e) Vehicle Emission Test Sequence

1) Transient Driving Cycle

The vehicle shall be driven over the driving cycle contained in Section 276. Table A of this Part.

Driving Trace

The inspector shall follow an electronic, visual depiction of the time/speed relationship of the transient driving cycle (hereinafter, the trace). The visual depiction of the trace shall be of sufficient magnification and adequate detail to allow accurate tracking by the driver and shall permit the driver to anticipate upcoming speed changes. The trace shall also clearly indicate gear shifts as specified in subsection (e)(3) of this Section.

# NOTICE OF ADOPTED AMENDMENTS

## 3) Shift Schedule

For vehicles with manual transmissions, inspectors shall shift gears according to the following shift schedule:

Shift-Sequence	Approximate Speed	Nominal Cycle Time
Gear	Miles Per Hour	Seconds
1-2	15	<del>9.3</del>
2-3	<del>25</del>	4 <del>7.0</del>
De-eluteh	15	<del>87.9</del>
1-2	15	<del>101.6</del>
2-3	25	105.5
<del>3-2</del>	<del>17</del>	119.0
2-3	<del>25</del>	145.8
3-4	40	<del>163.6</del>
4-5	45	<del>167.0</del>
<del>5-6</del>	<del>50</del>	<del>180.0</del>
<del>De-clutch</del>	<del>15</del>	<del>234.5</del>

Gear shifts shall occur at the points in the driving cycle where the specified speeds are obtained. For vehicles with fewer than 6 forward gears, the same schedule shall be followed with shifts above the highest gear disregarded.

# 4) Speed excursion limits shall apply as follows:

- A) The upper limit is 2 mph higher than the highest point on the trace within 1 second of the given time.
- B) The lower limit is 2 mph lower than the lowest point on the trace within 1 second of the given time.
- C) Speed variations greater than the tolerances (such as may occur during gear changes) are acceptable provided that they occur for no more than 2 seconds on any occasion.
- D) Speeds lower than those prescribed during the underpowered

## NOTICE OF ADOPTED AMENDMENTS

intervals of seconds 4 through 18, 97 through 115, and 154 through 219 of the trace will allow the station supervisory personnel the option of overriding the automatic void of the test. As part of the override, the station supervisory personnel will be required to witness a second trace.

- i) During the station supervisory personnel's witness of the second or subsequent trace, the test will be aborted if a speed variation exists for more than two seconds on any occasion outside the underpowered intervals. If this condition is detected, the test shall be stopped, and may be restarted, or aborted and rejected.
- ii) If a speed lower than those prescribed during the underpowered intervals is detected, the vehicle will have the opportunity to regain the test trace speed. Once the test trace speed is attained, the vehicle will be required to meet the speed excursion limitations for the entirety of the trace, outside the underpowered intervals.
- iii) Station supervisory personnel overrides can be used to accept the results of the witnessed second or subsequent trace(s) if the override is flagged with a trace statistic or distance error so long as it meets the requirements specified in subsections (e)(4)(D)(i) and (e)(4)(D)(ii).
- E) The test shall be aborted and immediately restarted if speed excursion limits are exceeded, except as described in subsection (e)(4)(D) of this Section.
- 5) Speed Variation Limits

The speed variation limits shall be determined by one of the following methods:

- A) Linear Regression Method
  - i) A linear regression of feedback value on reference value

# NOTICE OF ADOPTED AMENDMENTS

shall be performed on each transient driving cycle for each speed using the method of least squares, with the best fit equation having the form: y = mx + b, where:

y = The feedback (actual) value of speed

m = The slope of the regression line

x = The reference value

b = The y intercept of the regression line

ii) The SE of y on x shall be calculated for each regression line. A transient driving cycle lasting the full 240 seconds that exceeds the following criteria shall be void and the test shall be repeated:

SE = 2.0 mph maximum

m = 0.96 - 1.01

 $r^2 = 0.97 \text{ minimum}$ 

b = 2.0 -mph

iii) A transient driving cycle that ends before the full 240 seconds that exceeds the following criteria shall be void and the test shall be repeated:

SE = (Reserved)

m = (Reserved)

 $r^2 = (Reserved)$ 

b = (Reserved)

- B) Positive Kinetic Energy (PKE) Method
  - i) The speed variation limits shall be determined by the following equation for Positive Kinetic Energy (PKE):

$$\frac{1}{2} \frac{1}{2} \frac{1}$$

where:

## NOTICE OF ADOPTED AMENDMENTS

 $PP_t = V_t^2 - V_{t+1}^2 mi^2 / hr^2 for V_t > V_{t+1}$ 

 $PP_t = 0 \text{ for } V_t \le 0$ x = distance (miles)

PP<sub>t</sub> = Positive Specific Power at time t

V<sub>t</sub> = Velocity at time t V<sub>t+</sub> = Velocity at time t 1

ii) A transient driving cycle lasting the full 240 seconds with a PKE value that is below the lower PKE limit for passing vehicles or above the upper limit for failing vehicles shall be void and the test shall be repeated:

Upper Limit: PKE > 3456 mi/hr<sup>2</sup> Lower Limit: PKE < 3082 mi/hr<sup>2</sup>

- iii) A transient driving cycle that ends before the full 240 seconds with a PKE value that is below the lower second-by-second PKE limit for passing vehicles or above the upper second-by-second PKE limit for failing vehicles shall be void and the test shall be repeated. The second-by-second upper and lower PKE limits are specified in Section 276. Table B.
- iv) PKE values shall not be used to make early pass/fail determination.
- 6) The actual distance traveled for the transient driving cycle shall be measured. If the absolute difference between the measured distance and the theoretical distance for the actual test exceeds 0.05 miles, the test shall be void and shall be repeated.
- 7) The vehicle shall be rejected if, during the course of the transient loaded mode test, station supervisory personnel verify that the test cannot be completed due to the mechanical condition of the vehicle.
- 8) Inertia Weight Selection

Operation of the inertia weight selected for the vehicle shall be verified as

## NOTICE OF ADOPTED AMENDMENTS

specified in Section 276.506(a) of this Part. For systems employing electrical inertia simulation, an algorithm identifying the actual inertia force applied during the transient driving cycle shall be used to determined proper inertia simulation.

The CVS operation shall be verified for each test for a CFV-type CVS by measuring either the absolute pressure difference across the venturi or measuring the blower vacuum behind the venturi for minimum levels needed to maintain choke flow for the venturi design. The operation of an SSV-type CVS shall be verified throughout the test by monitoring the difference in pressure between upstream and throat pressure. The minimum values shall be determined from system calibrations. Monitored pressure differences below the minimum values shall void the test, and a test lane system lockout shall be initiated. No further testing shall be done until the problem is corrected by station supervisory personnel. At Official Inspection Stations, the vehicle involved shall be immediately retested in a properly operating lane.

f) Transient Loaded Mode Exhaust Gas Test Score Calculations

The transient loaded mode exhaust gas test score shall be determined according to the method specified in 40 CFR 85.2205(b) (Draft), incorporated by reference in Section 276.104(a) of this Part, with the following exceptions:

The Phase 2 secres for the test shall be determined by dividing the sum of the mass of each pollutant obtained in each second of the Phase 2 test by the number of miles driven in the Phase 2 test. The first data point is the sample taken from t=94 to t=95. The Phase 2 test score shall be determined by the following equation:

$$\frac{\Sigma}{\Sigma} = \frac{\text{grams of emissions}}{\text{grams of emissions}}$$

$$\frac{Phase 2 \text{ gpm}}{t} = \frac{t-94}{t}$$

$$\frac{S}{\Sigma} = \frac{\text{miles traveled}}{t=94}$$

Where s = duration of test in seconds for fast pass, or

## ENVIRONMENTAL PROTECTION AGENCY

## NOTICE OF ADOPTED AMENDMENTS

s = 239 seconds for complete transient loaded mode exhaust gas test.

- 2) NO<sub>xe</sub> nitrogen oxide concentration of the dilute exhaust sample as measured in ppm and multiplied by 1.03.
- 3) NO<sub>xd</sub> = background nitrogen oxide concentration of the dilution air,
  sampled as described in 40 CFR 85.2221(b)(5) (Draft),
  incorporated by reference in Section 276.104(a) of this Part, as
  measured in ppm and multiplied by 1.03.

# g) Pass/Fail Determination

Compliance with the transient loaded mode exhaust emission test shall be made in accordance with the standards contained in 35 III. Adm. Code 240, Subpart E.

(Source: Repealed at 35 III. Reg. 11268, effective June 28, 2011)

## Section 276.209 On-Board Diagnostic Test Procedures

- Test Procedures
  The OBD test procedure shall be conducted according to the method specified in
  40 CFR 85.2222(a), (b), and (c), incorporated by reference in Section 276.104(be)
  of this Part. However, once initiated, the OBD test shall be conducted as
  completely as possible, regardless of intermediate reject or fail results.
- b) Pass/Fail Determination
  The pass/fail determination for OBD testing shall be conducted according to the method specified in 40 CFR 85.2222(d), incorporated by reference in Section 276.104(be) of this Part.
- c) Reject Determination

  The reject determination for OBD testing shall be conducted according to the method specified in 40 CFR 85.2222(c), incorporated by reference in Section 276.104(b) of this Part, with the following modifications, according to which a

#### NOTICE OF ADOPTED AMENDMENTS

vehicle shall be rejected from testing:

- 1) The the vehicle is presented for testing and passes the OBD inspection, but the number of unset non-continuous OBD readiness codes exceeds the following:
  - A) 2 monitors "not ready" for MY 1996 to MY 2000 vehicles and
  - B) 1 monitor "not ready" for MY 2001 and newer vehicles; or
- 2) The the vehicle is presented for retesting after an OBD failure involving catalytic converter DTCs P0420 through P0439, and the catalyst monitor is "not ready" at the time of retest.
- d) OBD Test Report

The OBD test report shall be prepared according to the method specified in 40 CFR 85.2223, incorporated by reference in Section 276.104(<u>be</u>) of this Part., with the exception that the following statement shall be added to the report for all OBD tests conducted prior to January 1, 2002, in accordance with 35 III. Adm. Code 240.191:

"At the present time, passing the OBD test is not a requirement for passing the Enhanced I/M test. Therefore, this information is being provided strictly as an aid in diagnosing emission related problems."

AGENCY NOTE: No vehicle shall fail the I/M test on the basis of the OBD test until January 1, 2002, in accordance with 35 III. Adm. Code 240.191.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

SUBPART C: EMISSIONS COMPLIANCESTICKER OR CERTIFICATE ISSUANCE, DISPLAY, AND POSSESSION

# Section 276.301 General Requirements

a) The owners of all vehicles subject to inspection shall obtain and display on the vehicle a valid unexpired vehicle emissions inspection sticker, or carry within the

## NOTICE OF ADOPTED AMENDMENTS

vehicle a valid unexpired vehicle emissions compliance inspection certificate from the Agency, whichever is required by the Agency and issued in the manner described in this Section.

- b) The owner of every vehicle which receives an emissions inspection sticker or certificate shall be required to have the vehicle inspected prior to the expiration date of the sticker or certificate, and shall be requested to have the vehicle inspected prior to the end of the Assigned Test Month.
- be) Failure to comply with applicable provisions of the Vehicle Emissions Inspection Law [625 ILCS 5/Ch. 13A] or the Vehicle Emissions Inspection Law of 20051995 [625 ILCS 5/Ch. 13CB] (shall subject the ownersowner(s) of the vehicle to the enforcement provisions thereof.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.303 Emissions <u>Compliance Inspection Sticker or Certificate Design and Content</u>

All emissions <u>compliance</u>inspection stickers or certificates required under this Section shall, at a minimum, include the following information in a clear and recognizable fashion:

- a) The statement "Registration Renewal Authorized" the month and year the sticker or compliance certificate expires;
- b) The the TED (month and year) in which the vehicle is next scheduled for testing; and.
- c) Aa unique emissions or compliance certificate number; and-
- d) The following vehicle information:
  - 1) VIN;
  - 2) License plate number;
  - 3) Vehicle model year; and

## NOTICE OF ADOPTED AMENDMENTS

#### 4) Vehicle make.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.304 Initial Emissions Inspection Stickers or Certificates (Repealed)

The Initial Emissions Inspection Sticker or Certificate enables a vehicle not previously subject to inspection to display a valid sticker or possess a valid certificate within the vehicle to demonstrate compliance with the Vehicle Emissions Inspection Law or the Vehicle Emissions Inspection Law of 1995 pending such vehicle receiving an initial emissions inspection. Such sticker or certificate shall be issued as follows:

- a) The Agency or its designee shall send Initial Emissions Inspection Stickers or Certificates to owners of all vehicles initially subject to inspection no less than fifteen days prior to the first day of the month in which the vehicle is scheduled for its initial inspection. Each Initial Emissions Inspection Sticker or Certificate shall expire on the last day of the third month following the month assigned by the Agency for the initial inspection.
- b) Each Initial Emissions Inspection Sticker or Certificate shall include a notice of the assigned month of the initial emissions inspection and shall be accompanied by a clear statement from the Agency that, based on vehicle records, the vehicle is subject to applicable emissions inspection requirements of the Vehicle Emissions Inspection Law of 1995, as applicable. A form accompanying the sticker or certificate will be provided to the vehicle owner to allow for correction of any information relied upon by the Agency.

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

## Section 276.305 Exempt Emissions Inspection Stickers or Certificates (Repealed)

- a) An Exempt Emissions Inspection Sticker or Certificate may be issued by the Agency or its designee for each vehicle registered in an Affected County that either:
  - 1) is exempt from emissions inspection pursuant to Section 13B-15f of the Vehicle Emissions Inspection Law of 1995; or

#### ENVIRONMENTAL PROTECTION AGENCY

## NOTICE OF ADOPTED AMENDMENTS

- 2) is exempt from emissions inspection pursuant to Section 13B-15(g) of the Vehicle Emissions Inspection Law of 1995, provided however, that in order to receive an exemption under Section 13B-15(g), the owner of the vehicle must provide sufficient proof to the Agency that the vehicle is not located and primarily operated within an Affected County.
- b) Each Exempt Emissions Inspection Sticker or Certificate shall, at a minimum, include the following information in a clear and recognizable fashion:
  - 1) A unique sticker or certificate number;
  - 2) the word "EXEMPT"; and
  - 3) the month and year the sticker or certificate expires, if applicable.

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

## Section 276.306 Renewal Emissions Inspection Stickers or Certificates (Repealed)

\_A Renewal Emissions Inspection Sticker or Certificate will be issued by the Agency or its designee to the owner of each vehicle which successfully passes a vehicle emissions test. Each Renewal Emissions Inspection Sticker or Certificate will contain the information indicated in Section 276.303 and the word "PASS".

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

#### Section 276.307 Temporary Emissions Inspection Stickers or Certificates (Repealed)

- a) The Agency or its designee may issue a Temporary Emissions Inspection Sticker or Certificate for any vehicle subject to inspection which currently has a valid Renewal or Initial Emissions Inspection Sticker or Certificate, and for which an Initial Emissions Inspection Sticker or Certificate has already been issued.
- b) A Temporary Emissions Inspection Sticker or Certificate may only be issued if the vehicle's owner informs the Agency that the vehicle will be tested by the end of the seventh month after the vehicle's Assigned Test Month, and one or more of the following conditions exist:

#### ENVIRONMENTAL PROTECTION AGENCY

# NOTICE OF ADOPTED AMENDMENTS

- the vehicle is located and being primarily operated in an area not currently subject to inspection under the Vehicle Emissions Inspection Law;
- 2) the vehicle is inoperative or has failed a vehicle emissions inspection and is awaiting necessary repairs to enable the vehicle to comply; or
- 3) the vehicle has not received necessary repairs or adjustments for which it is eligible under any emissions performance warranty provided pursuant to Section 207 of the Clean Air Act.
- c) A Temporary Emissions Inspection Sticker or Certificate shall be issued and contain a sticker or certificate expiration date which is the end of the seventh complete month after the Assigned Test Month.
- d) A Temporary Emissions Inspection Sticker or Certificate may only be issued to the owner of a vehicle once in the vehicle's test cycle.

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.308 Corrected or Interim Emissions Inspection Stickers or Certificates (Repealed)

Vehicles subject to emissions inspection which have previously been issued an Initial Emissions Inspection Sticker or Certificate and which have an Assigned Test Month may be reassigned to a later Assigned Test Month. Whenever such reassignment is approved by the Agency, the Agency or its designee shall issue a Corrected or Interim Emissions Inspection Sticker or Certificate to the owner of the vehicle.

- a) The Agency shall issue a Corrected or Interim Emissions Inspection Sticker or Certificate for a vehicle if one or more of the following conditions exist:
  - the Agency is notified by the Secretary of State that the vehicle has been registered by a new owner and the Agency assigns a test month for the vehicle that is later than the currently Assigned Test Month in order for the registered owner of the vehicle to receive proper notice to have the vehicle tested:
  - 2) the Agency finds it necessary to reassign vehicles to a later Assigned Test

#### ENVIRONMENTAL PROTECTION AGENCY

#### NOTICE OF ADOPTED AMENDMENTS

Month and year in order to implement the Vehicle Emissions Inspection Law of 1995; or

- 3) the vehicle is assigned a new test month and year as a result of the granting of a petition pursuant to Section 276.311.
- b) All Corrected or Interim Emissions Inspection Stickers or Certificates shall expire at the end of the third month following the Assigned Test Month.

(Source: Repealed at 35 III. Reg. 11268, effective June 28, 2011)

## Section 276.309 Waiver Emissions Inspection Stickers or Certificates (Repealed)

A Waiver Emissions Inspection Sticker or Certificate shall be issued by the Agency to the owner of any vehicle which fails a vehicle emissions test and at least one retest but successfully complies with the applicable waiver requirements of Section 276.401. Each Waiver Emissions Inspection Sticker or Certificate will contain the information indicated in Section 276.303 and the word "WAIVER".

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.310 Emissions Inspection Sticker and Certificate Display and Possession (Repealed)

- a) If an emissions inspection sticker required by this Part is issued by the Agency or its designee to the owner of a vehicle, it shall be affixed to the lower left hand side of the vehicle's windshield as viewed by the driver facing toward the front of the vehicle. Such sticker shall be affixed so as not to obscure the Vehicle Identification Number (VIN) of the vehicle when viewed from the outside. No more than one emission inspection sticker shall be displayed at any time. If an emissions inspection certificate required by this Part is issued by the Agency or its designee, it shall be carried inside the vehicle for which it is issued.
- b) Any sticker or certificate issued and required to be affixed to or possessed within a vehicle subject to inspection under the Vehicle Emissions Inspection Law, whether expired or unexpired, shall not be removed by any person for any reason. If the sticker or certificate is damaged or destroyed a duplicate sticker or certificate shall be requested from the Agency or its designee and issued to the

## NOTICE OF ADOPTED AMENDMENTS

owner of the vehicle.

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

## Section 276.311 Change of Assigned Test Month (Repealed)

Any person who is unable to have his or her vehicle tested in the month assigned by the Agency may request a permanent change of the Vehicle's Assigned Test Month. The Agency may grant the request, reassign the vehicle's Assigned Test Month, and issue a Corrected Emissions Inspection Sticker or Certificate as follows:

- a) if a vehicle is unable to be tested by the end of the seventh month after its

  Assigned Test Month, and is not eligible for an exemption under Section 276.305

  nor covered by reciprocity provisions of Subpart J, a new test month will be
  assigned based on the month the vehicle will return to an Affected County; and
- b) if the vehicle is in storage during the month of October, November, December, January, February or March, the vehicle will be assigned a test month of the following April, May, or June if the request is received prior to the sticker or certificate expiration date.

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.312 Economic Hardship Extension Stickers or Certificates (Repealed)

An Economic Hardship Extension Sticker or Certificate shall be issued by the Agency to the owner(s) of any vehicle that fails a vehicle emissions test but successfully complies with the applicable economic hardship extension requirements of Section 276.404 of this Part. Each Economic Hardship Extension Emissions Inspection Sticker or Certificate will contain the information indicated in Section 276.303 and the words "ECONOMIC HARDSHIP EXTENSION".

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

SUBPART D: WAIVER, AND ECONOMIC HARDSHIP EXTENSION, AND OUTSIDE OF AFFECTED COUNTIES ANNUAL EXEMPTION REQUIREMENTS

Section 276.401 Waiver Requirements

#### NOTICE OF ADOPTED AMENDMENTS

- All vehicles subject to inspection under the Vehicle Emissions Inspection Law of 20051995 [625 ILCS 5/Ch.-13CB] shall be eligible for a waiver from meeting the applicable vehicle emission standards contained in 35 Ill. Adm. Code 240 upon submission of proof to a Waiver Inspector of compliance with all of the following:
  - <u>Afterafter</u> failing a retest, the vehicle has failed to comply with the applicable vehicle emission standards;
  - <u>As</u> minimum expenditure of at least \$450 in emission-related repairs exclusive of tampering-related repairs have been made;
  - <u>Thethe</u> vehicle has received all repairs and adjustments for which it is eligible under any emission performance warranty provisions pursuant to Section 207 of the Clean Air Act (42 USC 7541);
- d) the repairs have resulted in an improvement in vehicle emissions as determined by comparison of initial and final retest results;
  - <u>4e</u>) <u>The the Agency determines by normal inspection procedures that the emission control devices are present and appear to be properly connected and operating;</u>
  - <u>S</u>f) Repairs for vehicles of model year 1981 and later are conducted by a recognized repair technician; and
  - <u>Evidence evidence</u> of repair is presented consisting of either <u>of the following:</u>
    - A) Signedsigned and dated receipts identifying the vehicle and describing the diagnostic procedures that were utilized in determining the repairs, justification that the repairs performed were appropriate and necessary for the emissions test failure, and thework performed and amount charged for eligible emission-related repairs; repairs, or
    - <u>B)</u> Anen affidavit executed by the person performing the eligible

#### NOTICE OF ADOPTED AMENDMENTS

emission related repairs.

- b) Emission-related repairs performed not more than 30 days prior to the current TED may be applied to the \$450 minimum expenditure if the repairs were appropriate for the DTCs present at the time of the initial failure.
- c) Waivers shall not be issued if the MIL is inoperative.
- <u>Vehicles subject to a steady-state idle exhaust test shall not be eligible for waivers unless the vehicle passes a fuel cap test.</u>
- e) Waivers shall be issued to the vehicle owners. In the event the vehicle owner is not present, a waiver may be issued to the vehicle owner's designee if specific written authorization from the vehicle owner on a form prescribed by the Agency is presented at the time of waiver application.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

#### Section 276,403 Denial or Issuance of Waiver

- a) If the Agency determines that an applicant for a waiver has not complied with all applicable waiver criteria set forth in Section 276.401 of this Part, the waiver request shall be denied. The Agency shall provide to the applicant a written statement containing the reasons for the denial.
- b) If the Agency determines that an applicant for a waiver has complied with all waiver criteria set forth in Section 276.401 of this Part, the waiver shall be issued. The Agency shall provide to the applicant an emissions compliance certificate of waiver-containing, at a minimum, the information described in Section 276.303 a description of the vehicle, including the manufacturer's vehicle identification number; the issuance date of the waiver; and the expiration date of the waiver.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

## Section 276.404 Economic Hardship Extension Requirements

The Agency shall issue a one year emissions compliance certificate to the owner of a vehicle that meets the requirements of subsection (a) of the Section.

## ENVIRONMENTAL PROTECTION AGENCY

#### NOTICE OF ADOPTED AMENDMENTS

## a) Requirements

A one year economic hardship extension sticker or certificate shall be granted by the Agency to the owner(s) of a vehicle upon application if the following criteria are met:

- 1) When when tested, the subject vehicle failed to meet applicable emission standards contained in 35 Ill. Adm. Code 240, except that the economic hardship extension sticker or certificate will not be granted if only the applicable fuel cap emissions test standard contained in 35 Ill. Adm. 240 is failed;
- The the registered owner or ownersowner(s) of the subject vehicle certifies that his or her, or their, household income qualifies as "low income" as defined in this Part. In the case of multiple registered owners who are not part of the same household, the registered owners must certify that the sum of each registered owner's household income qualifies as "low income" as defined in Section 276.102 of this Part;
- The the current or former ownerowner(s) of a subject vehicle has not previously received an emissions compliance certificate for economic hardship extension sticker or certificate for the subject vehicle, or, if an emissions compliance certificate for economic hardship extension has previously been issued, the vehicle passed all required emissions tests prior to issuance of another emissions compliance certificate for economic hardship extension sticker or certificate;
- 4) The the registered owner owner(s) of the subject vehicle presents present(s) either of the following, which shall not include any costs associated with any motor vehicle emission related recall that has been, or is to be, paid by a manufacturer or dealer:
  - A) Ae written estimate prepared by a recognized repair technician for emission related vehicle repairs, parts or services, including diagnostic fees, related to the emissions test failure, in the amount of 50 percent or greater of the current waiver repair minimum amount contained in Section 276.4012(a)(23) of this Part; or

#### NOTICE OF ADOPTED AMENDMENTS

- B) <u>If the registered ownerowner(s)</u> intends to perform the necessary services or repairs, the written estimate shall include only the cost of emission related parts;
- Thethe registered ownerowner(s) of the vehicle grants authorization to the Agency or its representatives to make legitimate inquiries as necessary, including to all relevant State departments or agencies, including but not limited to the IllinoisOffice of the Secretary of State and the Department of Human Services, to verify ownership and income information.
- b) An emissions compliance certificate issued under this Sectioneconomic hardship extension sticker or certificate is not transferable to one or more subsequent owners.
- c) An emissions compliance certificate issued under this Sectioneconomic hardship extension sticker or certificate may be revoked by the Agency if the Agency determines that the applicant or applicantsapplicant(s) made false statements on the economic hardship extension application.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

## Section 276.405 Outside of Affected Counties Annual Exemption Requirements

- a) The owner of a vehicle that is located and being primarily operated outside of the affected counties, or in other jurisdictions in which vehicle emission inspections are not required, may be issued a one year emissions compliance certificate allowing the motorist to renew the registration without having an emissions inspection. Written proof of the vehicle's location must be provided by one of the following:
  - 1) Tax bill:
  - 2) Utility bill;
  - 3) Tuition bill;
  - 4) Storage receipt;

## NOTICE OF ADOPTED AMENDMENTS

- 5) Military orders: or
- 6) Other written proof deemed acceptable by the Agency.
- b) Vehicles obtaining a one year emissions compliance certificate under this Section will be subject to inspection by the next TBD unless the motorist complies with subsection (a) of this Section.
- A vehicle owner who is currently in the military and deployed outside the affected counties may be issued a one year emissions compliance certificate under this Section if written proof as specified in Section 276.405(a)(5) or (a)(6) is provided.

(Source: Added at 35 III. Reg. 11268, effective June 28, 2011)

SUBPART E: TEST EQUIPMENT SPECIFICATIONS

## Section 276.501 General Requirements

Compliance with Illinois vehicle <u>testexhaust and evaporative emissions</u> standards shall be determined by <u>following the test procedures set forth in Subpart B of this Part and by utilizingsampling vehicle exhaust and evaporative emissions with the following:</u>

- a) Steady-state idle test equipment meeting the specifications set forth in Sections 276.502 and 276.503 of this Part and the evaporative; b) Evaporative system test equipment meeting the specifications set forth in Section 276.504 of this Part; or
- e) Transient loaded mode test equipment meeting the specifications set forth in Sections 276.505 and 276.506 of this Part;
- bd) On-road remote sensing test equipment meeting the specifications set forth in Section 276.507 of this Part; orand
- <u>ce</u>) OBD test equipment meeting the specifications set forth in Section 276.508 of this Part.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

#### ENVIRONMENTAL PROTECTION AGENCY

## NOTICE OF ADOPTED AMENDMENTS

# Section 276.502 Steady-State Idle Exhaust Test Analysis Systems Functional Requirements

The steady-state idle test exhaust test analysis system shall meet the functional requirements specified in 40 CFR 85.2225(b)-(Draft), incorporated by reference in Section 276.104(a) of this Part with the following exception: the sampling system shall have both a tachometer and a dynamometer. Additionally, all exhaust gas analyzers used at Official Inspection Stations shall be capable of:

- a) <u>Provideproviding</u> reliable, continuous service under high throughput (i.e., 25 tests per hour minimum) conditions;
- b) <u>Makemaking</u> an automatic selection of the proper emission standard for each vehicle tested;
- c) <u>Makemaking</u> automatic pass/fail determinations for each vehicle tested;
- d) Recordrecording test data in machine-readable (computer) form for subsequent data processing and analysis; and
- e) Makemaking an instantaneous printing of duplicate copies of test results.; and
- f) meeting the following equipment calibration requirements:
  - 1) automatic HC hangup check with purging to begin upon completion of each test;
  - 2) automatic zero and span check to be conducted prior to each test:
  - 3) automatic leak check within 4 hours prior to the test; and
  - 4) automatic 2-point gas calibration within 4-hours prior to the test.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

# Section 276.503 Steady-State Idle Test Exhaust Test Analysis Systems Performance Criteria

The steady-state idle test exhaust test analysis system shall meet the performance criteria


## ENVIRONMENTAL PROTECTION AGENCY

## NOTICE OF ADOPTED AMENDMENTS

specified in 40 CFR 85.2225(c)-(Draft), incorporated by reference in Section 276.104(a) of this Part.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.504 Evaporative System Integrity Test Functional Requirements and Performance Criteria



6)

Pressurized pressurized using air, Nitrogen (N<sub>2</sub>), or an equivalent non-

## NOTICE OF ADOPTED AMENDMENTS

toxic, non-greenhouse, inert gas;

- 7) <u>Capable capable</u> of controlling the supply pressure and preventing over pressurization;
- 8) <u>Tampertamper</u> resistant; and
- 9) <u>Designed designed</u> to avoid damage to the vehicle during installation, testing and removal.
- b) Fuel cap pressure decay tester

  The fuel cap pressure decay tester used for evaporative system integrity testing shall be equipped with a pressure gauge with a minimum range of 0 to 50 inches of water and an accuracy of 0.3 inches of water or 2 percent of point, whichever is greater.
- c) Fuel cap leak flow tester

  The fuel cap leak flow tester used for evaporative system integrity testing shall
  be:
  - 1) <u>Equipped equipped</u> with a serviceable air filter upstream of the flow comparison circuitry;
  - 2) <u>Equipped equipped</u> with an automatic shutoff and a low-battery indicator if battery powered;
  - 3) <u>Supplied supplied</u> with a NIST traceable reference passing fuel cap of nominal 52 to 56 cc/min for <u>dailydaly</u> test verification;
  - 4) <u>Supplied supplied</u> with a NIST traceable reference failing fuel cap of nominal 64 to 68 cc/min for daily test verification;
  - 5) Accurate accurate to 3 cc/min at the 60 min flow standard; and
  - 6) <u>Ableable</u> to be modified, either by the manufacturer or an authorized service center, to test at a revised leakage (flow) rate from that originally shipped.

## ENVIRONMENTAL PROTECTION AGENCY

## NOTICE OF ADOPTED AMENDMENTS

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

# Section 276.505 Transient Loaded Mode Test Systems Functional Requirements (Repealed)

The transient loaded mode test system shall meet the functional requirements specified in 40 CFR 51.358(b), incorporated by reference in Section 276.104(d) of this Part.

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

## Section 276.506 Transient Loaded Mode Test Systems Performance Criteria (Repealed)

a) Dynamometer Specifications

The dynamometer system shall meet the performance criteria specified in 40 CFR 85.2226(a) (Draft), incorporated by reference in Section 276.104(a) of this Part, with the following exceptions:

- 1) the inertia simulation capability need not be any higher than 5500 pounds;
- 2) the dead weight method is not required for the torque meter or load cell calibration; and
- the vehicle cooling fan is required equipment for all transient loaded mode test systems.
- b) Constant Volume Sampler Specifications

The constant volume sampler system shall meet the performance criteria specified in 40 CFR 85.2226(b) (Draft), incorporated by reference in Section 276.104(a) of this Part.

e) Analytical Instruments Specifications

The analytical instruments shall meet the performance criteria specified in 40 CFR 85.2226(c) (Draft), incorporated by reference in Section 276.104(a) of this Part, with one exception: the NO<sub>x</sub> measurement shall be determined by measuring nitrogen oxide and multiplying this value by 1.03. The measurement

#### NOTICE OF ADOPTED AMENDMENTS

of nitrogen dioxide is not required.

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.507 On-Road Remote Sensing Test Systems Functional Requirements and Performance Criteria

- a) The on-road remote sensing test equipment shall consist of the following:
  - Anan infrared SDM capable of measuring the concentration of HC, CO, and CO<sub>2</sub> present in an in-use vehicle;
  - 2) Aa camera system that automatically photographs vehicle license plates;
  - 3) An system that links each emission record to the correct vehicle license plate photograph; and
  - 4) And laser based speed and acceleration measurement system.
- b) The Infrared SDM shall be of a design certified to meet the following accuracy requirements:

Pollutant	Range	Accuracy
НС	ALL	±150 ppm or ±15 percent of expected HC Concentration
CO	≤ 3.0 percent	±10 percent or 0.25 percent (Whichever is greater)
	> 3.0 percent	±15 percent

c) The speed and acceleration measurement system shall be of a design certified to measure vehicle speed to within  $\pm 0.5$  miles per hour and vehicle acceleration to within  $\pm 0.3$  miles per hour per second at the moment exhaust is measured.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

## NOTICE OF ADOPTED AMENDMENTS

# Section 276.508 On-Board Diagnostic Test Systems Functional Requirements and Performance Criteria

The OBD test system shall meet the functional requirements specified in 40 CFR 85.2231, incorporated by reference in Section 276.104(be) of this Part.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

# SUBPART F: EQUIPMENT MAINTENANCE AND CALIBRATION

## Section 276.602 Steady-State Idle Test Equipment Calibration

All operators of steady-state idle test-exhaust test gas analyzers shall comply with the following calibration and operating procedures unless alternative procedures have been approved by the Agency:

- a) Exhaustexhaust gas analyzers shall be warmed up prior to each vehicle inspection, zero check, span check, or calibration. Analyzers shall be considered to be in a warmed-up condition once stabilized zero readings (readings stabilize for one minute within ±2 percent of full scale, low range on all 3 channels) are obtained.
- b) The analyzer shall conduct a zero and span check prior to each test. The span check shall include the HC, CO and CO<sub>2</sub> channels, and the NO and O<sub>2</sub> channels, if present. If zero and/or span drift cause the signal levels to move beyond the adjustment range of the analyzer, it shall lock out from testing.
- c) The system shall lock out from testing if sample flow falls below 3 percent of full scale, or causes system response time to exceed 13 seconds to 90 percent of a step change in input, whichever is less.
- d) A system leak check shall be performed within 244 hours before the test, and may be performed in conjunction with the gas calibration described in subsection (e)(1) of this Section. If a leak check is not performed within 244 hours or if the analyzer fails the leak check, the analyzer shall lock out from testing. The leak check shall be a procedure demonstrated to effectively check the sample hose and probe for leaks and shall be performed in accordance with good engineering practices. An error of more than +2 percent of the reading using low range span gas shall cause the analyzer to lock out from testing and shall require repair of

#### ENVIRONMENTAL PROTECTION AGENCY

#### NOTICE OF ADOPTED AMENDMENTS

leaks.

- e) Gas Calibration
  - 1) Analyzers must undergo a two-point calibration within 72 hours before each test unless changes in barometric pressure are compensated for automatically and statistical process control demonstrates equal or better quality control using different frequenciesOn each operating day, analyzers shall successfully pass a two-point gas calibration for HC, CO, and CO2 and shall continually compensate for changes in barometric pressure. Calibration shall be checked within 4 hours before the test and the analyzer adjusted if the reading is more than 2 percent different from the span-gas value. Gas calibration shall be accomplished by introducing span gas that meets the requirements of subsection (e)(3) of this Section into the analyzer through the calibration port. If the analyzer reads the span gas within the allowable tolerancetolerence range (i.e., the square root sum of the squares of the span gas tolerance described in subsection (e)(3) of this Section and the calibration tolerance, which shall be equal to 2 percent), no adjustment of the analyzer is necessary. The gas calibration procedure shall correct readings that exceed the allowable tolerance range to the center of the allowable tolerance range. The pressure in the sample cell shall be the same with the calibration gas flowing during calibration as with the sample gas flowing during sampling. If the system is not calibrated, or the system fails the calibration check, the analyzer shall lock out from testing.
  - 2) A two point gas calibration procedure shall be followed. The span shall be accomplished at one of the following pairs of span points:
    - A) Low

300 – ppm propane (HC)

1.0 - percent CO

6.0 - percent CO<sub>2</sub>

1000 – ppm nitric oxide (if equipped with NO)

High

1200 – ppm propane (HC)

#### NOTICE OF ADOPTED AMENDMENTS

4.0 – percent CO 12.0 – percent CO<sub>2</sub> 3000 – ppm nitric oxide (if equipped with NO)

#### B) Low

0 - ppm propane (HC) 0.0 - percent CO 0.0 - percent CO<sub>2</sub> 0 - ppm nitric oxide (if equipped with NO)

High
600 – ppm propane (HC)
1.6 – percent CO
11.0 – percent CO<sub>2</sub>
1200 – ppm nitric oxide (if equipped with NO)

- 3) The span gases used for the gas calibration shall be traceable to NIST standards within two percent and shall be within two percent of the span points specified in subsection (e)(2) of this Section.
- f) Other Checks

In addition to the other periodic checks described in this Section, those described in subsections (f)(1) and (f)(2) of this Section shall also be used to verify system performance under the special circumstances described therein.

- 1) Gas Calibration
  - A) Each time the analyzer electronic or optical systems are repaired or replaced, a gas calibration shall be performed prior to returning the unit to service.
  - B) MultiMonthly multi-point calibrations shall be performed every 6 months. The calibration curve is checked at 20 percent, 40 percent, 60 percent, and 80 percent of full scale, and must be adjusted or repaired if the specifications in Section 276.503 are not met.

#### ENVIRONMENTAL PROTECTION AGENCY

#### NOTICE OF ADOPTED AMENDMENTS

2) Leak Checks
Each time the sample line integrity is broken, a leak check shall be performed prior to testing.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

#### Section 276.604 Record Keeping

All operators of emissions test equipment shall maintain written records of all-maintenance and calibration records pertaining to emission test equipment shall be submitted to the Agency, as required, upon request performed on such equipment. Said records shall be kept on site for a period of two years and shall be made available to the Agency upon request.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

# Section 276.605 Transient Loaded Mode Test Equipment Maintenance and Calibration (Repealed)

a) General Requirements

The transient loaded mode test equipment shall meet the general maintenance and ealibration requirements specified in 40 CFR-85.2234(a) (Draft), incorporated by reference in Section 276.104(a) of this Part.

b) Dynamometer

The dynamometer equipment shall meet the maintenance and calibration requirements specified in 40 CFR 85.2234(b) (Draft), incorporated by reference in Section 276.104(a) of this Part.

c) Constant Volume Sampler

The constant volume sampler test equipment shall meet the maintenance and calibration requirements specified in 40 CFR 85.2234(e) (Draft), incorporated by reference in Section 276.104(a) of this Part, with one exception: The bag sample check described in 40 CFR 85.2234(c)(6) (Draft), incorporated by reference in Section 276.104(b) of this Part, shall be performed during initial acceptance testing.

#### NOTICE OF ADOPTED AMENDMENTS

#### d) Analysis System

The transient loaded mode test analysis system shall meet the maintenance and calibration requirements specified in 40 CFR 85.2234(d) (Draft), incorporated by reference in Section 276.104(a) of this Part, with the following exceptions:

- the zero and up-scale span points shall be checked at 2 hour instead of 3 hour intervals following the daily mid-scale curve check;
- 2) the NO<sub>x</sub> converter check and the NO/NO<sub>x</sub> flow balance are not required;
- 3) the integrator check as specified in 40 CFR 85.2234(d)(9) (Draft), incorporated by reference in Section 276.104(b) of this Part, is required; and
- 4) the interference check (laboratory testing) as specified in 40 CFR 85.2234(d)(11) (Draft), incorporated by reference in Section 276.104(b) of this Part, is required to be performed instead of the interference check specified in 40 CFR 85.2234(d)(11) (Draft), incorporated by reference in Section 276.104(a) of this Part.

#### e) Gases

The transient loaded mode test analysis system gases shall meet the calibration requirements specified in 40 CFR 85.2234(e) (Draft), incorporated by reference in Section 276.104(a) of this Part.

#### f) Overall System Performance

The overall system performance for the transient loaded mode test shall meet the requirements specified in 40 CFR 85.2234(f) (Draft), incorporated by reference in Section 276.104(a) of this Part.

#### g) Control Charts

The transient loaded mode test analysis system control charts shall meet the requirements specified in 40 CFR 85.2234(g) (Draft), incorporated by reference in Section 276.104(a) of this Part, with the following exception: combined control charts for all facilities will be maintained.

#### NOTICE OF ADOPTED AMENDMENTS

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

SUBPART G: FLEET SELF TESTING REQUIREMENTS

#### Section 276.701 General Requirements

- a) Any owner or lessee of a fleet of 15 or more vehicles subject to inspection may apply to the Agency for a permit to <u>establish and</u> operate one or more <u>private</u> official inspection <u>Private Official Inspection (stations for the limited purpose of self-testing their fleet of vehicles Stations Fleet Inspection Permit).</u>
- b) Vehicle inspections shall be conducted in accordance with Subpart B of this Part, as applicable. Fleet inventory vehicles shall be required to receive the same emissions tests as vehicles tested at an Official Inspection Station. However, for a period not to exceed 5 years after implementation of the Enhanced I/M testing program as described in Section 276.101(b) of this Part, fleet self-testers who have been issued and maintain a valid fleet inspection permit ("fleet inspection permittees") prior to implementation of the Enhanced I/M testing program shall be allowed to conduct steady-state idle exhaust tests only on vehicles required to receive such tests under Section 13B-25(c) of the Vehicle Emissions Inspection Law of 1995 using currently approved steady state idle test equipment and steady state idle equipment maintenance and calibration procedures. This authority shall terminate for each such fleet inspection permittee prior to the expiration of this 5 year period if such permittee discontinues fleet self-testing. Beginning with the implementation of the Enhanced I/M testing program, fleet inspection permittees utilizing the authority of this subsection to conduct steadystate idle exhaust tests shall also conduct evaporative system integrity tests as described in Sections 276.205, 276.504 and 276.603 of this Part, and shall also conduct on board diagnostic tests as described in Sections 276,209, 276,508, and 276.607 of this Part as applicable. Such fleet inspection permittees shall not substitute a steady state idle exhaust test for the transient loaded mode exhaust test required to be performed on vehicles specified by Section 13B-25(b) of the Vehicle Emissions Inspection Law of 1995.
- c) If the Agency substantially amends emissions <u>testinspection</u> standards, procedures, or other requirements, it may require emissions inspectors to be recertified and fleet self-testers to be re-permitted.

#### NOTICE OF ADOPTED AMENDMENTS

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

## Section 276.702 Fleet Inspection Permit

The Agency <u>mayshall</u> issue <u>fleet inspection permits</u> Fleet Inspection Permits to eligible applicants upon a showing of compliance with the following requirements:

- a) Equipment
  All fleet inspections shall be conducted utilizing equipment approved by the
  Agency. This equipment shall meet that meets the same functional requirements,
  performance criteria, maintenance standards, and calibration requirements as
  specified in Subparts E and F of this Partequipment used in Official Inspection
  Stations.
- b) Training
  Each fleet inspector shall be required to complete and pass a training course given
  by the Agency covering the following topics:
  - 1) I/M rules and regulations;
  - 2) <u>Testing</u>testing procedures;
  - 3) Analyzeranalyzer use;
  - 4) Analyzeranalyzer calibration and quality control; and
  - 5) <u>Datadata</u> recording, record keeping and submittal.
- c) General Fleet Inspection Permit Requirements
  - Applicants shall submit an application for a fleet inspection permit for each inspection location on forms provided by the Agency and shall include a list of vehicles that will be inspected at the private official inspection station.
  - 2) Applicants shall execute a fleet inspection agreement.

#### ENVIRONMENTAL PROTECTION AGENCY

- 31) Fleet inspection permits issued by the Agency Inspection Permits shall expire two years after the date of issuance.
- 42) Fleet inspection permits laspection Permits are not transferable.
- Any change in the name and/or address of any permittee or any fleet inspector or inspectors inspector(s) employed by the permittee shall be reported to the Agency in writing on forms provided by the Agency within 30 days after the change.
- 6) A permittee may request, and the Agency may grant, a relocation of equipment at a private official inspection station.
- d) Fleet Inspection Permit Suspension and Revocation
  For the following reasons, the Agency may suspend for a period of up to two
  years or revoke, with the permittee being ineligible to reapply for two years, a
  fleet inspection permitFleet Inspection Permit:
  - 1) <u>Thethe permittee has violated any applicable laws, rules, or regulationsprovision of this rule;</u>
  - 2) <u>Thethe permittee has provided false or misleading information in its application for a fleet inspection permitFleet Inspection Permit;</u>
  - the permittee has failed to keep proper records as required by the Agency in that: i)the permittee has failed to notify the Agency of a vehicle's emissions test results within 45 days after the date of inspection; ii) Thethe permittee has failed to notify the Agency that a vehicle has been proposed to be added or deleted from its vehicle inventory within the time specified by the Agency; 60 days after the vehicle's disposal; or
  - 4iii) 20 percent or more of the vehicles in the permittee's fleet have <u>failed to comply with the Vehicle Emissions Inspection Law of 2005expired compliance stickers or certificates</u>;
  - 54) The the permittee has misrepresented any information provided in fleet vehicle lists, vehicle inspection reports, and/or equipment maintenance and calibration reports;

#### NOTICE OF ADOPTED AMENDMENTS

<u>65</u>) <u>The the number of vehicles subject to inspection in the permittee's fleet becomes less than 15.</u>

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

#### Section 276.703 Fleet Inspection Permittee Operating Requirements

- a) Vehicle Eligibility
  - The permittee shall furnish the Agency with a list of all vehicles subject to inspection and for which fleet inspection is requested. The Agency shall provide forms to the permittee shall provide this list to the Agency for the purpose of establishing a fleet vehicle inventory and requesting vehicle inspection dates. The information shall be submitted to the Agency either on the forms supplied, or by electronic media and shall include, at a minimum, in the following:
    - $\underline{A}$ )  $\underline{VIN}$ ;
    - B) License plate number;
    - C) Vehicle make:
    - D) Vehicle model; and
    - E) Vehicle model year. format required by the Agency. When the Agency approves or denies the fleet vehicle inspection dates, it shall notify the fleet tester and, if approved, provide test forms to the fleet for submission to the Agency after testing.
  - The permittee shall notify the Agency in writing on forms provided by the Agency or by electronic media in the format required by the Agency in the event that any vehicles in the fleet inventory are proposed to be added or deleted from its vehicle inventory within the time specified by the Agencysold or otherwise removed from fleet service. This notification shall be made within 30 days after the end of the month the vehicle is

# NOTICE OF ADOPTED AMENDMENTS

#### removed from fleet service.

Junless authorized by the Agency, vehicles contained in the fleet vehicle inventory pursuant to subsection (a) of this Section shall only be inspected at private official inspection stations Private Official Inspection Stations. If authorization is given by the Agency for a vehicle contained in the fleet vehicle inventory to be tested or retested at an official inspection station Official Inspection Station, any subsequent retests in that vehicle's testing cycle shall be conducted at an official inspection station Official Inspection Station.

# b) Inspection Frequency/Scheduling At a minimum, all All vehicles in the fleet inventory shall be inspected biennially. Upon Agency approval, the Assigned Test Months and sticker or compliance certificate expiration dates become compliance deadlines for use in program enforcement. Agency approval shall be based on the availability of personnel to audit the performance of inspections and the ability of the fleet operators to meet the proposed schedule (this will be determined by the number of vehicles to be inspected and the number of inspectors available).

- c) Inspection <u>ResultsReports and Stickers or Certificates</u>
  All inspection results shall be submitted to the Agency electronically.
  - 1) A Vehicle Inspection Report shall be submitted to the Agency for each vehicle that passes or fails an emissions inspection. Inspection results shall be reported on forms provided by the Agency. Inspection results shall be submitted to the Agency within 45 days after the date of inspection.
  - Pollowing review and processing, the Agency shall validate inspection stickers or certificates for all vehicles complying with program requirements. If the Agency determines that a vehicle inspection report is deficient, a sticker or certificate will not be validated and it shall return the inspection report along with instructions to correct the identified deficiencies.
  - The permittee shall be responsible for the security and accountability of all vehicle inspection stickers or certificates issued to the permittee. In the

#### ENVIRONMENTAL PROTECTION AGENCY

#### NOTICE OF ADOPTED AMENDMENTS

event of lost or stolen stickers or certificates, the permittee shall notify the Agency in writing within 10 business days. Failure to report missing stickers or certificates shall be grounds for suspension or revocation of a Fleet Inspection Permit.

- 4) Inspection stickers or certificates shall be displayed or possessed in accordance with Section 276.310.
- 5) The permittee shall retain a legible copy of each completed Vehicle Inspection Report for a minimum of two years after the date of inspection. The reports shall be made available for Agency review upon request during normal business hours.
- d) Equipment, Maintenance and Calibration

  1)All equipment used for emissions testing in <u>private official inspection</u>

  <u>stationsPrivate Official Inspection Stations</u> shall meet the functional requirements,

  and performance criteria, <u>maintenance standards</u>, and <u>calibration requirements</u>

  contained in Subparts E and F of this Part.
  - The permittee shall keep records of all calibrations, leak checks, and other maintenance performed on emissions inspection equipment for two years. The records shall be retained at the fleet facility.

All records shall be kept on standardized forms provided by the Agency and shall be made available for Agency review upon request during normal business hours.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

#### Section 276.704 Private Official Inspection Station Auditing and Surveillance

- a) All private official inspection stations shall be equipped with surveillance equipment as specified in the fleet inspection agreement referenced in Section 276.702(c)(2).
- b) The Agency may, on an unscheduled and unannounced basis, during normal business hours, conduct an audit inspection of any <u>private official inspection</u> stations Private Official Inspection Stations to determine if inspection equipment

#### ENVIRONMENTAL PROTECTION AGENCY

#### NOTICE OF ADOPTED AMENDMENTS

is properly operating and calibrated, to review vehicle inspection reports and maintenance records, and to check inspector proficiency. During the course of the audit inspection, the Agency representative may take one or more of the following actions:

- <u>Requirerequire</u> that, if any vehicle emissions test equipment, calibration equipment, or related materials fails to perform as required, <u>the such</u> item shall be removed from service until corrective action is taken;
- <u>Thethe</u> fleet inspector may be required to perform an emissions inspection on a fleet vehicle. If no fleet vehicles are available, the fleet inspector may be required to perform an emissions inspection on an Agency vehicle.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

#### SUBPART H: GRIEVANCE PROCEDURE

#### Section 276.802 Procedure for Filing Grievance

- a) Grievances shall be filed with the Agency within 30 days after the decision made by the Agency.
- b) Grievances shall be made in writing on petition forms provided by the Agency.
- c) Grievance <u>petition</u> forms and instructions shall be available at all <u>full-service</u> official inspection stationsOfficial Inspection Stations and by mail from the Agency.
- d) Original repair orders, receipts, and other pertinent documentation shall be submitted with the grievance petition.
- e) Grievances and supporting documentation shall be mailed to the Agency at the address specified on the grievance petition.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

#### Section 276.803 Agency Investigation

#### NOTICE OF ADOPTED AMENDMENTS

- a) The Director of the Agency or the Director's designee shall appoint an Agency employee to investigate every grievance regarding the failure of an emissions test or the denial of a waiver submitted to the Agency in accordance with this Part.
- b) The Agency's investigation shall be concluded within 45 days after the receipt of the grievance <u>petitionform</u>.
- within the 45 day investigation period, the Agency shall <u>submitissue written</u> notification to the <u>petitioner</u>, and affected inspector or station, its written <u>determination</u> indicating the Agency's determination as to the correctness or incorrectness of the decision <u>thatwhich</u> precipitated the grievance. In conducting the investigation, the Agency may require the petitioner to present the vehicle for inspection by the Agency or its designated agent.
- d) The Agency's written <u>determination notification</u> shall include a statement of the facts relied upon and the legal and technical issues decided by the Agency in making its determinations.
- e) The Agency's written <u>determination</u> motification may also require that an employee of the Agency or its designee:
  - 1) <u>Issue issue</u> an emissions <u>compliance inspection sticker or certificate</u>;
  - 2) Reinspectreinspect the vehicle;
  - 3) <u>Applyapply</u> the standards that the Agency has determined to be applicable; or
  - 4) Taketake any other action that the Agency deems to be appropriate.
- f) If the Agency's investigation determines that a part needed to complete the necessary and appropriate repairs is unavailable after contacting at least 3 independent sources, one of which shall be the original equipment manufacturer, a waiver may be granted.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

SUBPART I: NOTICES

#### NOTICE OF ADOPTED AMENDMENTS

#### Section 276.901 General Requirements

The Agency shall send a vehicle emissions test notice an Initial Emissions Inspection Notice and, when appropriate, a Warning Notice to owners of vehicles subject to inspection that which shall includestate the TED Assigned Test Month of the initial emissions inspection and be accompanied by a clear statement from the Agency that, based on vehicle records, the vehicle is subject to inspection under the Vehicle Emissions Inspection Law of 20051995. A form accompanying the explanation will be provided to the vehicle owner to allow for correction of any information relied upon by the Agency.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

#### Section 276.902 Vehicle Initial Emissions Test Inspection Notice

At least 15 days <u>afterprior to</u> the beginning of the <u>TEDAssigned Test Month</u>, the Agency shall send a <u>vehicle emissions test notice</u> an <u>Initial Emissions Inspection Notice</u> to the registered <u>owner ofowner</u> the vehicle requesting that the vehicle be tested <u>during the Assigned Test Month</u>. This <u>vehicle emissions test noticeInitial Emissions Inspection Notice</u> shall include the following <u>information</u>:

- a) an Initial Emissions Inspection Sticker or Certificate, or a Corrected or Interim Emissions Inspection Sticker or Certificate, if required;
- <u>ab</u>) <u>Information relating to the operation of official inspection stations addresses and operating hours of Official Inspection Stations;</u>
- be) Agency vehicle emissions test program contact informationa form or eard to be returned to the Agency indicating the reasons the owner believes that the vehicle should not be subject to inspection pursuant to the Vehicle Emissions Inspection Law of 1995, or cannot comply by the expiration date;
- cd) Briefbrief explanation of the program; and
- de) Instructions instructions for vehicle inspections.

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

#### NOTICE OF ADOPTED AMENDMENTS

#### Section 276.903 Warning Notice (Repealed)

If a vehicle has not complied with the provisions of the Vehicle Emissions Inspection Law of 1995 within two months before the sticker or certificate expiration date, the Agency shall send a Warning Notice to the vehicle's owner at the registration address currently on file with the Agency. The Warning Notice shall include the following information:

- a) the addresses of Official Inspection Stations near the registration address of the vehicle:
- b) a form or card to be returned to the Agency indicating the reasons the owner believes that the vehicle should not be subject to inspection under the Vehicle Emissions Inspection Law of 1995, or cannot comply by its expiration date; and
- c) <u>a statement of potential penalties for failure to comply with the requirements of</u> the Vehicle Emissions Inspection Law of 1995, or this Part, as applicable.

(Source: Repealed at 35 III. Reg. 11268, effective June 28, 2011)

#### SUBPART J: RECIPROCITY WITH OTHER JURISDICTIONS

# Section 276.1001 Requirements for Vehicles Registered in Affected Counties and Located in Other Jurisdictions Requiring Vehicle Emissions Inspection

- a) Vehicles registered in the <u>affected counties</u> Affected Counties and located and being primarily operated in other jurisdictions requiring vehicle emission testing that will not be returning to an Affected County within 7 months after the vehicle's Assigned Test Month, or that are permanently located in such other jurisdiction, must be tested in that jurisdiction and comply with the such jurisdiction's emissions testing requirements and the vehicle's registered owner must comply with the following requirements:
  - <u>Uponupon</u> written notification from the Agency <u>and/or the Illinois</u>
    <u>Secretary of State</u> to the vehicle's registered owner to have the vehicle inspected, the vehicle must be presented for inspection in the jurisdiction where the vehicle is located; and
  - <u>2b</u>) <u>Whenwhen</u> the vehicle passes the inspection, receives a waiver or

#### NOTICE OF ADOPTED AMENDMENTS

exemption, or otherwise complies with the emissions inspection requirements of the jurisdiction in which the vehicle is located, the vehicle inspection report or other appropriate documentation must be forwarded to the Agency using the methodat the address stated on the vehicle emission testinspection notice.; and

<u>When when</u> the Agency receives the appropriate vehicle inspection report or other documentation, the vehicle inspection record will be updated to reflect compliance and the vehicle's registered owner will be issued an emission compliance certificate.

(Source: Amended at 35 Ill. Reg. 11268, effective June 28, 2011)

# Section 276.1002 Requirements for Vehicles Registered in Other Jurisdictions Requiring Vehicle Emissions Inspection and Located in an Affected County

Vehicles that which are registered in another jurisdiction that which requires vehicle emissions testing, and that which are located and being primarily used in an affected county Affected County, and that would be considered a non-exempt vehicle as defined in this Part, may be tested at a full service official inspection stationan Official Inspection Station in accordance with the following:

- a) The vehicle's registered owner shall obtain a voluntary test voucher from the Agency prior to inspection upon a written request for an emissions inspection by the vehicle's registered owner to the Agency, the Agency shall request appropriate vehicle and owner information necessary for testing;
- b) The vehicle's registered owner shall have the vehicle inspected if, upon review, the Agency determines the vehicle is eligible to receive an emissions inspection, the Agency shall notify the vehicle's registered owner (or one of the registered owners, if more than one) authorizing the vehicle to be tested at an Official Inspection Station; and
- c) Afterafter the vehicle has received an emissions inspection, the appropriate test results will be issued to the vehicle's registered owner for submission to the jurisdiction requiring emissions inspections and a sticker or certificate will be issued as appropriate.

#### NOTICE OF ADOPTED AMENDMENTS

(Source: Amended at 35 III. Reg. 11268, effective June 28, 2011)

#### SUBPART K: REPAIR FACILITY PERFORMANCE REPORTING

# Section 276.1101 Requirements for Collecting and Reporting Data Pertaining to the Repair of Vehicles that Failed or Were Rejected from an Emissions Inspection

- a) The Agency shall:
  - 1) Compile pertinent emissions repair data into a report that is provided to owners of vehicles that do not pass an emissions inspection and that is made available to the general public; and
  - 2) Specify the method for transmitting repair data to the Agency.
- b) Individuals or businesses that perform emissions-related repairs and report that data to the Agency shall:
  - Register at a website specified by the Agency and agree to be bound by the terms and conditions of any user agreement associated with that website:
  - 2) Submit accurate, complete, and legible repair data in order to be included in the compiled report; and
  - Perform a minimum number of repairs within a specified period of time and achieve a minimum performance level as determined by the Agency in order to be included in the compiled report.
- <u>An individual or business shall be excluded from the compiled report for not less</u> than one year if the Agency determines that:
  - 1) An individual or business has violated a user agreement as referenced in subsection (b)(1) of this Section;
  - 2) An individual or business has violated Illinois law or rule or any provision of a local ordinance, code, or rule relating to solicitation or advertisement of emission-related repair services;

#### ENVIRONMENTAL PROTECTION AGENCY

- An individual or business uses the Agency servicemark, Illinois Air Team servicemark, or Air Team servicemark; uses any reproduction, counterfeit, copy, variation, or imitation of these servicemarks; or uses the Agency, Illinois Air Team, or Air Team name in any of their advertisements, solicitations, or other marketing devices without prior written authorization of the Agency;
- 4) An individual or business directly or indirectly creates the impression that the Agency, Illinois Air Team, or Air Team endorses, approves, or recommends the emission-related repair services of the individual or business; or
- 5) An individual or business intentionally, negligently, or through gross negligence affects or attempts to affect the integrity of a vehicle emissions inspection or an inspection procedure.
- d) If the Agency determines that an individual or business has repeated any action listed in subsection (c) of this Section, the Agency may permanently exclude the individual or business from the compiled report.
- e) Agency Determinations, Disputes, and Appeals
  - Agency Determinations
    Agency determinations under subsection (c) or (d) of this Section shall be furnished in writing to the individual or business by mail, electronic mail, facsimile, personal service, or similar means.
  - 2) Disputes
    - A) An individual or business that disagrees with an Agency determination under subsection (c) or (d) of this Section may dispute that determination. Disputes shall:
      - i) Be in writing;
      - ii) Include a copy of the Agency's written determination:

#### NOTICE OF ADOPTED AMENDMENTS

- iii) Include a justification with any supporting documentation explaining why the individual or business should not be excluded from the compiled report; and
- iv) Be clearly marked "Repair Facility Performance Report Dispute".
- B) The written dispute must be postmarked within 30 days after the date of the Agency's determination.
- C) If the written dispute has not been disposed of by written agreement within 30 days after the postmarked date of the written dispute, the individual or business may appeal the Agency's determination to the Director in accordance with subsection (e)(3) of this Section.

#### 3) Appeals

- A) If a dispute is not disposed of by written agreement as specified in subsection (e)(2) of this Section, an individual or business may file a notice of appeal with the Director of the Agency.
- B) A notice of appeal shall:
  - i) Be in writing;
  - ii) Include a copy of the Agency's written determination;
  - iii) Include a copy of the written dispute;
  - iv) Include any additional justification with any supporting documentation explaining why the individual or business should not be excluded from the compiled report; and
  - v) Be clearly marked "Repair Facility Performance Report Appeal".

#### NOTICE OF ADOPTED AMENDMENTS

- C) The notice of appeal must be postmarked within 60 days after the postmarked date of the written dispute.
- D) The appeal shall be decided by the Director, or his or her authorized representative, who shall render a decision in writing.

  This decision shall be furnished to the individual or business by mail, electronic mail, facsimile, personal service, or similar means.

  The decision of the Director shall be final and conclusive.
- E) The Director shall not be precluded from considering questions of law or equity in any decision.

(Source: Added at 35 Ill. Reg. 11268, effective June 28, 2011)

#### NOTICE OF ADOPTED AMENDMENTS

# Section 276.TABLE A Transient Driving Cycle (Repealed)

Time	Speed
(second)	(mph)
0	0 0
1	0
2	0
3	0
4	0
5	3
6	5.9
7	<del>8.6</del>
8	11.5
9	14.3
10	16.9
11	<del>17.3</del>
<del>12</del>	18.1
13	20.7
14	21.7
<del>15</del>	22.4
16	22.5
<del>17</del>	22.1
18	21.5
19	20.9
<del>20</del>	20.4
21	19.8
<del>22</del>	<del>17.0</del>
23	14.9
24	14.9
25	15.2
<del>26</del>	<del>15.5</del>
<del>27</del>	16.0
<del>28</del>	17.1
<del>29</del>	<del>19.1</del>
<del>30</del>	21.1
31	<del>22.7</del>
32	<del>22.9</del>

33	22.7
34	22.6
35	21.3
36	19.0
<del>37</del>	17.1
<del>38</del>	15.8
3.9	15.8
40	<del>17.7</del>
41	19.8
<del>42</del>	21.6
43	23.2
44	24.2
45	<del>24.6</del>
46	24.9
47	25.0
48	25.7
49	<del>26.</del> 1
<del>50</del>	26.7
51	27.5
<del>52</del>	<del>28.6</del>
53	29.3
54	29.8
<del>55</del>	<del>30.1</del>
<del>56</del>	30.4
<del>57</del>	<del>30.7</del>
<del>5</del> &	<del>30.7</del>
<del>5</del> 9	<del>30.5</del>
60	<del>30.</del> 4
64	30.3
62	<del>30.</del> 4
<del>63</del>	<del>30.8</del>
64	<del>30.4</del>
65	<del>29.9</del>
66	<del>29.5</del>
<del>67</del>	<del>29.8</del>
68	30.3
69	30.7
70	<del>30.9</del>

71	31.0
<del>72</del>	30.9
73	30.4
<del>74</del>	<del>29.8</del>
<del>75</del>	<u> 29.9</u>
<del>76</del>	30.2
77	30.7
<del>78</del>	31.2
79	31.8
80	32.2
81	32.4
82	<del>32.2</del>
83	31.7
84	<del>28.6</del>
85	<del>25.1</del>
86	21.6
87	18.1
88	14.6
80	11.1
90	7.6
46	4.1
92	0.6
93	0
94	0
<del>95</del>	0
<del>96</del>	0
97	0
<del>ઇ</del> ક	3.3
99	6.6
100	e.e
101	13.2
102	16.5
103	19.8
104	22.2
105	24.3
106	<del>25.8</del>
107	26.4
108	<del>25.7</del>

109	<del>25.1</del>
110	24.7
111	25.2
112	<del>25.</del> 4
113	27.2
114	26.5
115	24.0
116	22.7
<del>117</del>	<del>19.4</del>
118	17.7
<del>119</del>	17.2
120	<del>18.1</del>
121	<del>18.6</del>
122	20.0
123	20.7
124	21.7
125	22.4
<del>126</del>	22.5
127	<del>22.1</del>
128	21.5
129	<del>20.9</del>
130	20.4
131	19.8
<del>132</del>	17.0
133	<del>17.1</del>
134	15.8
135	45.8
<del>136</del>	17.7
137	19.8
138	21.6
139	<del>22.2</del>
140	24.5
141	24.7
142	24.8
143	<del>24.7</del>
144	24.6
145	24.6
146	<del>25.1</del>

147	<del>25.6</del>
148	25.7
149	25.4
4-50	24.9
151	25.0
<del>152</del>	<del>25.4</del>
153	26.0
154	<del>26.0</del>
155	25.7
<del>156</del>	<del>26.1</del>
157	<del>26.7</del>
158	27.3
159	30.5
<del>160</del>	33.5
161	<del>36.2</del>
162	37.3
163	39.3
164	40.5
165	42.1
166	43.5
167	45-1
168	46.0
169	46.8
170	47.5
171	47.5
<del>172</del>	47.3
173	47.2
174	47.2
175	47.4
176	47.9
177	48.5
178	49.1
179	49.5
<del>180</del>	50.0
<del>181</del>	<del>50.6</del>
182	<del>51.0</del>
183	<del>51.5</del>
184	<del>52,2</del>
•	

## ENVIRONMENTAL PROTECTION AGENCY

185	<del>53.2</del>
186	<del>54.1</del>
187	54.6
188	54.9
189	<del>55.0</del>
190	<del>54.9</del>
191	54.6
<del>192</del>	<del>54.6</del>
193	<del>54.8</del>
194	<del>55.1</del>
195	<del>55.5</del>
<del>196</del>	<del>55.7</del>
<del>197</del>	<del>56.1</del>
198	<del>56.3</del>
199	<del>56.6</del>
200	<del>56.7</del>
201	<del>56.7</del>
<del>202</del>	<del>56.3</del>
203	<del>56.0</del>
204	<del>55.0</del>
205	<del>53.4</del>
206	51.6
207	51.8
208	<del>52.1</del>
209	<del>52.5</del>
210	<del>53.0</del>
211	<del>53.5</del>
212	<del>54.0</del>
213	<del>54.9</del>
214	<del>55.4</del>
<del>215</del>	<del>55.6</del>
<del>216</del>	<del>56.0</del>
217	<del>56.0</del>
218	<del>55.</del> 8
219	<del>55.2</del>
220	<del>54.5</del>
221	53.6
222	<del>52.5</del>

# NOTICE OF ADOPTED AMENDMENTS

<del>223</del>	<del>51.5</del>
224	<del>50.5</del>
<del>225</del>	48.0
226	44.5
227	41.0
228	37.5
229	<del>34.0</del>
230	30.5
234	<del>27.0</del>
232	23.5
233	20.0
234	16.5
235	<del>13.0</del>
236	9,5
<del>237</del>	6.0
238	2.5
<del>239</del>	0

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)

#### NOTICE OF ADOPTED AMENDMENTS

# Section 276.TABLE B Fast-Pass Speed Variation Limits Using Positive Kinetic Energy (PKE) Measurements (Repealed)

## Cumulative PKE Limits

Comment	Υ	<b>*</b> T
Second	<u>Lower</u>	Upper 7250
<del>30</del>	4 <del>621</del>	<del>7359</del>
<del>31</del>	4820	7664
<del>32</del>	4650	7380
33	4446	7045
34	<del>4261</del>	6739
35	4100	6474
36	<del>3968</del>	<del>625</del> 4
<del>37</del>	<del>3856</del>	6068
38	<del>3759</del>	<del>5905</del>
39	<del>3667</del>	<del>5750</del>
40	<del>3849</del>	<del>6026</del>
41	4074	<del>6367</del>
<del>42</del>	4258	<del>6643</del>
43	4409	<del>6867</del>
44	4451	<del>6920</del>
45	4383	<del>6802</del>
46	4300	<del>6663</del>
47	4188	6478
48	4183	6460
4 <del>9</del>	4128	<del>636</del> 4
<del>50</del>	4109	<del>6323</del>
<del>51</del>	4124	6336
<del>52</del>	4190	6426
<del>53</del>	4186	6410
54	<del>4150</del>	6343
<del>55</del>	4082	<del>622</del> 8
<del>56</del>	4 <del>017</del>	<del>6119</del>
<del>57</del>	<del>3956</del>	6015
<del>58</del>	<del>3851</del>	<del>5846</del>
<del>59</del>	<del>3752</del>	<del>5</del> 686
60	<del>3659</del>	5535

61	3571	5393
<del>62</del>	<del>3501</del>	<del>5278</del>
63	3474	5230
64	3397	5104
65	<del>3323</del>	4985
66	3255	4874
67	<del>3225</del>	4821
68	<del>3220</del>	4 <del>806</del>
69	3204	4774
<del>70</del>	3164	4707
71	3114	4624
70	<del>3055</del>	4529
<del>73</del>	<del>2999</del>	4438
74	<del>2946</del>	4352
75	<del>2906</del>	4285
76	<del>2887</del>	4251
<del>77</del>	2890	4248
<del>78</del>	<del>2893</del>	4245
<del>79</del>	<del>2907</del>	4258
80	2899	4239
81	2871	4191
82	2824	4116
83	<del>2779</del>	4044
84	2740	3980
<del>85</del>	<del>2708</del>	<del>3926</del>
86	<del>2680</del>	3880
87	<del>2658</del>	384 <u>2</u>
88	<del>2642</del>	3811
89	<del>2630</del>	3787
<del>90</del>	<del>2622</del>	3770
<del>91</del>	2619	3760
<del>92</del>	<del>2621</del>	3 <del>756</del>
93	<del>262</del> 4	3754
94	2627	3751
95	<del>2629</del>	3749
<del>96</del>	<del>2632</del>	3746
97	<del>263</del> 4	3743
98	2649	3757

<del>99</del>	<del>2691</del>	3811
100	<del>2760</del>	3902
101	<del>2856</del>	4031
102	2978	4196
103	<del>3125</del>	4396
104	<del>3238</del>	<del>45</del> 47
<del>105</del>	<del>3342</del>	4685
<del>106</del>	<del>3409</del>	4772
107	<del>3415</del>	4771
<del>108</del>	<del>3378</del>	4712
109	3344	4 <del>656</del>
<del>110</del>	<del>3310</del>	<del>4602</del>
111	<del>3310</del>	4 <del>59</del> 4
<del>112</del>	3290	4558
113	<del>3377</del>	4672
114	<del>3342</del>	4 <del>616</del>
115	<del>3312</del>	4 <del>566</del>
116	3284	4 <del>520</del>
117	<del>3261</del>	4481
<del>118</del>	<del>3241</del>	4445
<del>119</del>	<del>3221</del>	4411
120	3240	4429
121	<del>3241</del>	4423
122	<del>3284</del>	4474
123	<del>32</del> 94	4481
124	<del>3320</del>	4 <del>509</del>
125	<del>333</del> 1	<del>4516</del>
<del>126</del>	<del>3311</del>	4481
127	<del>3286</del>	4440
128	3262	4401
<del>129</del>	<del>3240</del>	4364
<del>130</del>	<del>3219</del>	4327
131	3108	4293
132	<del>3181</del>	4 <del>263</del>
133	<del>3168</del>	4239
134	3153	4211
135	<del>3138</del>	4184
<del>136</del>	<del>3192</del>	<del>42</del> 48

137	3259	4330
<del>138</del>	<del>3318</del>	4402
<del>139</del>	<del>3324</del>	4403
140	3414	<del>4515</del>
141	3399	4487
142	<del>3379</del>	4453
143	<del>3354</del>	4413
144	<del>3329</del>	4373
145	3 <del>305</del>	4334
<del>146</del>	<del>3306</del>	4329
147	<del>3308</del>	4323
148	3288	<del>4291</del>
149	<del>3265</del>	4253
<del>150</del>	3242	<del>4216</del>
<del>15</del> 1	<del>322</del> 4	4186
<del>152</del>	<del>3221</del>	4175
<del>15</del> 3	<del>322</del> 8	4177
<del>154</del>	<del>3205</del>	4141
155	3183	4105
156	<del>3181</del>	4095
157	<del>3188</del>	4098
<del>15</del> 8	<del>3195</del>	4101
<del>159</del>	3343	4283
160	3491	4465
<del>161</del>	<del>3630</del>	<del>4636</del>
162	3668	4676
<del>163</del>	<del>3769</del>	4 <del>796</del>
164	3814	4847
<del>165</del>	<del>3890</del>	4934
<del>166</del>	3 <del>95</del> 1	<del>500</del> 4
167	4029	5094
<del>168</del>	4053	5116
<del>169</del>	4 <del>069</del>	5127
<del>170</del>	4077	<del>5129</del>
<del>171</del>	4 <del>031</del>	5063
<del>172</del>	<del>3986</del>	4998
173	3942	4 <del>935</del>
174	3899	4874

175	<del>3872</del>	4832
<del>176</del>	<del>3868</del>	4818
177	3871	4814
<del>178</del>	<del>387</del> 4	4810
<del>179</del>	3862	4787
<del>180</del>	<del>3858</del>	4774
1-8-1	3 <del>861</del>	477 I
182	<del>3850</del>	4749
183	<del>3846</del>	4736
184	3857	4742
<del>185</del>	3890	4774
<del>186</del>	<del>3916</del>	4798
187	3 <del>911</del>	4784
188	389 <u>2</u>	4753
<del>189</del>	3 <del>858</del>	4704
<del>190</del>	<del>3818</del>	4647
<del>191</del>	<del>3779</del>	4592
<del>192</del>	<del>3740</del>	4538
<del>193</del>	<del>3717</del>	4502
194	<del>3701</del>	4475
195	<del>3692</del>	4458
<del>196</del>	3 <del>670</del>	4423
<del>197</del>	3 <del>662</del>	4406
198	3640	4373
<del>199</del>	3625	4348
<del>200</del>	3597	4307
201	<del>3563</del>	4259
202	<del>3530</del>	4213
203	3498	4167
204	<del>3467</del>	4123
<del>20</del> 5	3437	4082
<del>206</del>	3409	4042
<del>207</del>	<del>3393</del>	4016
<del>208</del>	3384	3998
209	3380	3987
210	<del>3382</del>	3984
211	3384	3980
212	3387	3976

## NOTICE OF ADOPTED AMENDMENTS

213	3412	<del>3999</del>
214	3414	<del>3995</del>
<del>215</del>	3399	<del>3970</del>
<del>216</del>	<del>3395</del>	<del>3959</del>
217	3368	<del>3921</del>
218	3341	3884
<del>219</del>	<del>3316</del>	<del>3848</del>
<del>220</del>	<del>3291</del>	3813
221	<del>3267</del>	<del>377</del> 8
<del>222</del>	<del>3243</del>	<del>3746</del>
<del>223</del>	<del>3221</del>	<del>3714</del>
224	<del>3200</del>	<del>3683</del>
<del>225</del>	3180	<del>365</del> 4
<del>226</del>	3162	<del>3627</del>
227	3145	<del>3603</del>
228	3131	<del>3580</del>
<del>229</del>	3118	<del>3560</del>
<del>230</del>	<del>3107</del>	3 <del>541</del>
<del>231</del>	<del>3096</del>	<del>3525</del>
<del>232</del>	3090	<del>3510</del>
<del>233</del>	<del>3084</del>	3496
<del>23</del> 4	<del>3079</del>	3487
<del>235</del>	<del>3076</del>	<del>3478</del>
<del>236</del>	<del>3075</del>	<del>3470</del>
<del>237</del>	<del>3075</del>	<del>3465</del>
<del>238</del>	3077	<del>3461</del>
<del>239</del>	3079	<del>3458</del>

(Source: Repealed at 35 Ill. Reg. 11268, effective June 28, 2011)